			4				3	7			2				1								
ı			I ON THIS DRA			DF CELESTRA, IS ED, USED OR		,	CELESTRA CAT.NO	W	RE SIZE	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01						
			T FOR WHICH						LB061401AF	CODE 2- #6 AWG	#6 Weld 61/24 =	1/4	1.64	0.45	0.08	1.00	0.26						
									260		24.6 kcmil												
D	NOT	≣:	SPE	CIFIED.		INCHES UNLES												D					
			LIST	ED BY "UN	DERWRITE	) J SERIES OF C ERS INC." AND "( EX/24 STRANDE	CSA" FOR USE		B V														
			OTH			' HAS NOT PEEF N THE SUFFIX C			- 98° 5°									_					
	MAT	ERIAL:	HIGI	H CONDUC.	TIVITY WR	OUGHT COPPE	3																
С	FINIS	SH:	SPE	CIFED PLA	TE PER MI	LESS OTHERWIS L - T -16366. " FOR SILVER.	SE		Beveled wire entry—— H									С					
									∕—Wire inspection hole														
$\rightarrow$		ALLATIO	ON GUIDE					-BOLT SIZE															
		COLOR :									e control of the cont				Die Çı	olor							
В	CUL)US ROHS								Color coded barrel markings									В					
			LIST WIRE CONF		2002/0																		
	-																						
										шп		ELES											
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.							n.							
Α										TITLE WIRE CONNECTORS AND SOLDERING													
									LUGS FOR CODE AND FLEX CABLE														
	$\vdash$		Ruby Feng							ATERIAL <b>HIGH-COND</b> WROUGHT (	COPPER LB061	101AP-26	0		TS	RID ANGLE PI	ROJECTION	ECTION					
ı	REV [	DATE	DWN	CHK		DESCR		,	ECN F	ELECTRO TIN	PLATE DWG. NO.	186-cp43	40   "	INIT IN	ICH -	<b>⊕</b> Ł							
			4				3	Ζ		2			1		1								