			4		1		3	7	7		2				1			
ı	DISCLOSE	D IN CO	NFIDENCE AND	O NOT TO BE		DF CELESTRA, IS ED, USED OR		,	CELESTRA CAT.NO		IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSED	EXCEP ¹	T FOR WHICH	FURNISHED.					LB063801AF		#6 Weld 61/24 =		1.83	0.58	0.06	1.00	0.27	
									261		24.6 kcmil							
D	NOT	Ε:		DIMENSION CIFIED.	NS ARE IN	INCHES UNLES	S OTHERWISE											D
			LIST	ED BY "UN	DERWRITE) J SERIES OF C ERS INC." AND "(EX/24 STRANDE	CSA" FOR USE		B									
			OTH			' HAS NOT PEEF N THE SUFFIX C			D D									
	MAT	ERIAL:	HIGI	H CONDUC	TIVITY WR	OUGHT COPPE	₹											
С	FINIS	SH:	SPE	CIFED PLA	TE PER MI	LESS OTHERWIS L - T -16366. " FOR SILVER.	SE		Beveled wire entry————————————————————————————————————									С
									—Wire inspection hole									
\rightarrow		ALLATION	ON GUIDE					BOLT SIZE									\leftarrow	
		COLOR :							The color									
В	C (UL) US ROHS,								Color coded barrel markings—									
			LIST		2002/95													
										HU		DELES						
									76. Huancun Rd. Zhongcun Town. www.huyaco.com Panyu Dist. Guangzhou 511495.							11.		
Α										WIRE CONNECTORS AND SOLDERING A								
									LUGS FOR CODE AND FLEX CABLE									
	\vdash		Ruby Feng				ards Spec. Initialed.			ATERIAL HIGH-COND WROUGHT (NISH	COPPER LB063	801AP-26	1	INIT	TS _	RID ANGLE PI	ROJECTION	
	REV [DATE	4	СНК		DESCR	3	/	N LCN	ELECTRO TIN	N PLATE	186-cp43	55 ິ I	IN	ICH 1	\P\ \	7	
			- ∓		I		J	_		_			1		'			