DISCLOSED IN CON	ON THIS DRAWING IS TH FIDENCE AND NOT TO B FOR WHICH FURNISHEE	HE PROERTY OF	CELESTRA, IS	1	1					1				
DISLOSED EXCEPT	FUR WHICH FURNISHEL	E REPRODUCE	D, USED OR		CELESTRA CAT.NO		IRE SIZE	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
).			DB041401A-260		40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	1/4	1.64	0.49	0.09	1.00	0.30	
NOTE:	1. ALL DIMENSIO SPECIFIED.	ONS ARE IN I	NCHES UNLESS	OTHERWISE										
-	ON CODE WIF	NDERWRITE RES AND FLE	J SERIES OF CA RS INC." AND "C X/24 STRANDED HAS NOT PEEP											
MATERIAL:	OTHERWISE S WITH "P".	SPECIFIED IN	I THE SUFFIX OF	THE CAT.NO.				۵ ^{۴⁶}		Ď				
FINISH:						Beveled wire entry								
INSTALLATION GUIDE DIE CODE = 29														
DIE COLOR =			/		¢						Die Co	nolo		
		RoH 2002/95/	S				Color co	ded ba	rrel ma	arkings				
	ZNVV/27/8 E513913													
						HUN www.huyac		76. Hua Panyu	ancun	Rd. Zh	nongcu	in Tow	'n.	
		ITTLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE												
00 23-Aug-25	Ruby Feng Sinia Qiu	L	Celestra Standar	ds Spec. Initialed.	MATE	MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER DB041401A-260 NTS THRID ANGLE PROJECTIO								
REV DATE	DWN CHK		DESCRI	PTION	ECN FINIS	ELECTRO TIN	DWG. NO.	186-cp43	367	INIT IN	СН	Ψt		