			_		1			_	<u></u>		_		İ					
		4 3 NFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS		3		<u>/</u>	2					1			.			
			I ON THIS DR <i>A</i> NFIDENCE ANI						CELESTRA		IRE SIZE	BOLT	В	C	D . 0 04.5	G	H	
			FOR WHICH						CAT.NO	CODE	FLEX		MIN	±0.04	±0.015	±0.02	±0.01	ł
									LB041458A	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	1/4	1.19	0.52	0.10	0.62	0.32	
_													!		ļ.		I.	D
D	N	IOTE:			NS ARE IN II	NCHES UNLES												
				CIFIED.														
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 								B ↓								
	ł																	
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								D D								
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry									С
			SUF	FIX CAT.NC).WITH "SP"	FOR SILVER.					′ ⊸ H ►							
										—Wire inspection hole								
\rightarrow	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray							BOLT SIZE									\leftarrow	
									-((D C							
В										Die Co	olor		В					
		CUL US ROHS							Color coded barrel markings									
			LIST WIRE CONF															
										шіі		ELES						
۸									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.							n.		
																		_
Α							_	WIRE CONNECTORS AND SOLDERING								Α		
								LUGS FOR CODE AND FLEX CABL							E			
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed	d.	N	ATERIAL HIGH-COND WROUGHT	SCALE NTS THRID ANGLE PR			ROJECTION	CTION			
1	REV	DATE	DWN	CHK		DESCR	IPTION		ECN F	NISH ELECTRO TII	N PLATE DWG. NO.	86-cp438	4	IN	CH	⊕ Ł		
			4				3		<u> </u>	2					1			
									ı									