					_													
		4			3			7 2			11					_		
ı			ON THIS DRA			CELESTRA, IS			CELESTRA		IRE SIZE	BOLT	В	С	D	G	Н	1 '
			FOR WHICH		NEI NODOCEI	D, OOLD ON			CAT.NO	CODE	FLEX		MIN	±0.04	±0.015	±0.02	±0.01	ļ.
									LB041434A	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil		1.31	0.56	0.09	0.75	0.32	
											133/.0177 49/.029							1
D																		D
	N	IOTE:			IS ARE IN II	NCHES UNLESS	OTHERWISE											
		SPECIFIED.																
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							B I									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																_	
			OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.															
		WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
	M	MATERIAL:																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry									С	
						FOR SILVER.		H										
										— Wire inspection hole								
\rightarrow	INSTALLATION GUIDE						— Wife inspection hole —BOLT SIZE									4		
		DIE CODE = 29 DIE COLOR = Gray								BOET GIZE								
		DIE GOLON = Glay																
									A		Ĭ							
_	⊸-G-⊸							-G>										
В																		В
		CUL) US ROHS							Color coded barrel markings—									
		L	LISTED)													
		ZM	VV/2/7/8.E513913															
	ł																	l —
		I	I						 		_	EL EC	ED A	005	\DQ=	\ ATI	201	
										HUYA® Www.huyaco.com CELESTRA CORPORATIO 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								
																	11.	
Α									-								Α	
,										WIRE CONNECTORS AND SOLDERING								
													AND FLEX CABLE					
	00	28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					i	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE LB041434A NT						D ANGLE PR	ROJECTION			
	REV	DATE	DWN	CHK		DESCR	PTION		ECN FII	NISH ELECTRO TI	N PLATE DWG. NO.	186-cp438	5 UN	iit INC	CH (→ E	<u></u>	
	4 3								2	•		Ì		1			·	
	•				'								•					