He BRACHAR LINC CH LING UNAV XG & HE MINCHT 'D CALESMA, B DROCKED & ACOUNT AND ALL BARKENDER, USE DA UNDECKED & ACOUNT AND ALL BARKENDER, USE DA UNDECKED & ACOUNT AND ALL BARKENDER, USE DA UNDER SPECIFIED. CELESTRA COUNT & N C L D A C H AL SZE WALL AND ALL BARKENDER, USE DA UNDER SPECIFIED. NOTE: 1. ALL DARENSKONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DARENSKONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 1. BIO4301A H4 AWG 4.00 H ALL BARKENDER, ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DARENSKONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 1. BIO4301A H4 AWG 3.0177.40/.021 3.01 0.02 0.03 MATERIAL: PHE-RIC AT NO.WITH '' HAN ONT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE OUT THE CATINO. WITH 'P. MATERIAL: DE COLOR - 0.01 0.01 0.32 MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIM PLATE UNLESS OTHERWISE SUFFIX CATINO.WITH 'SP-FOR SILVER. DE COLOR - 0.01 DE COLOR - 0.01 DE COLOR - 0.01 MATERIAL: MATERIAL: COLOR - 0.01 COLOR - 0.01 DE COLOR - 0.01 DE COLOR - 0.01 DE COLOR - 0.01 MATERIAL: COLOR - 0.01 COLOR - 0.01 COLOR - 0.01 DE COLOR - 0.			4				3	\checkmark	7		2				1		
Image: Note: 1. ALL DMENSIONS ARE IN INCHES UNLESS OTHERWISE SpecifieD. 3. ALL DAUBLALB, WP AND J SERIES OF CATINO'S ARE UNSTED BY UNDERWRITERS INC' AND CGA TORUSE ON CODE WRES AND FLEX/2013 STRANDED CABLES. PRE-FIX CAT NO.WITH 'L' HAS NOT FEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUPER NOT HER OFTER CATINO WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE FER MIL - 1- 16866. SUPER CAT NO WITH 'S' PFOR SILVER. WITH 'P'. INSTALLATION GUIDE DIE COOLE - 28 DIE COOLE - 38 DIE COOLE - 38 DIE COOLE - 48 DIE COOLE -	DISCLOS	GED IN CON	FIDENCE ANI	D NOT TO BE I	PROERTY OF	CELESTRA, IS D, USED OR							1	-	_	-	
SPECIFIED. 2. ALL DADE LUXPAND ADJ SERIES OF CATINO'S ARE LISTED BY 'UNDERWARTER'S INC: AND 'CSA' FOR USE ON CODE WRITER'S INC: AND 'CSA' FOR USE SUFFIX CAT NOWITH 'SP' FOR SILVER. INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 29 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 20 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 20 DIE COLOR = Gray INSTALLATION GUDE DIE CODE = 20 DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = Gray INSTALLATION GUDE DIE COLOR = GRAY INSTALLATION GUDE DIE COLOR = GRAY INSTALLATION GUDE DIE COLOR = GRAY INSTALLATION GUDE DIE COLOR = GRAY <	DISLOSE	DEAGEPT	FOR WHICH	FORNISHED.					LB043801A	#4 AWG	= 36.7 kcmil	3/8	1.98	0.59	0.09	1.00	0.32
INSTALLATION GUIDE DIE CODE CODE DIE CODE CODE MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIE DIAT THE SUFFIX COT THE CATINO. WITH "P: MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SUFFIX CAT NO.WITH "SP' FOR SILVER. NINSTALLATION GUIDE DIE CODE a 28 DIE CODE a 29 DIE COLOR = Gray Color coded barrel markings Color coded barrel markings Color coded barrel markings Celestra Standards Spec. Initialed. MIT PLY WIRE CONNECTORS AND SOLDERING UGS FOR CODE AND FLEX CABLE. WIRE MEMORATION BUIDE DIE OULD SIZE WWN.LUY4CO.COM Color coded barrel markings "I" WIRE CONNECTORS AND SOLDERING UGS FOR CODE AND FLEX CABLE WWN.LUY4CO.COM 0 23-Aug 28 Ruby Fong Sinia Glu 0 23-Aug 28 Ruby Fong Sinia Glu Celestra Standards Spec. Initialed. MATERY MEMORATION FOR SING CODE AND FLEX CABLE WIRE CONNECTORS AND SOLDERING WIRE WISH MEMORATION FOR SINGAL CODE AND FLEX CABLE		TE:	SPE	CIFIED.													
WITH *P: MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS SOTHERWISE SPECIED PLATE PERMIL-7-1636 Beveled wire entry HISTALLATION GUIDE Beveled wire entry DIE COLOR = Gray Bolt SIZE Color coded barrel markings Color coded barrel markings MATHIN MICHONOUTION Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel mark	-		LIST ON (PRE	ED BY "UNE CODE WIRE FIX CAT.NO	DERWRITEF S AND FLE D.WITH "L" F	RS INC." AND "C K/24 STRANDEI HAS NOT PEEP	SA" FOR USE CABLES. HOLE UNLESS						3				
SPECIFED PLATE PER MIL - T-16366. Beveled wire entry H SUFFIX CAT.NO.WITH 'SP' FOR SILVER. Wire inspection hole Die CODE = 29 Die CODE = 6ray Die CODE = 3 Gray Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel markings <t< td=""><td>MAT</td><td>TERIAL:</td><td>WIT</td><td>H "P".</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>so^{**°}</td><td></td><td>D</td><td></td><td></td><td></td></t<>	MAT	TERIAL:	WIT	H "P".								so ^{**°}		D			
INSTALLATION GUIDE DIE COLOR = Gray Image: Bolt Size Image: Bolt Size Image: Bolt Size Imag	FIN	ISH:	SPE	CIFED PLAT	TE PER MIL	- T -16366.	E		Bevele	ed wire entr	y H						
Image: Second	DIE	CODE =	29						/	Wire	•						
Color coded barrel markings Color coded barrel markings Celestra composition Celestra standards Spec. Initialed. Celestra Standards Spec. Initialed. Celes	DIE	COLOR =	= Gray			,			C								
ZMANGZYBE 553953 Image: Constraint of the standards of the s				US TED	RoH	Ş				œ−	-	oded ba	rrel ma	ırkings			
Image: Section of the section of th																	
Image: Construction of the construc		_										76. Hu	ancun	Rd. Zh	nongci	un Tow	
OU 23-Adg-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. WROUGHT COPPER LB043801A NTS REV DATE DWN CHK DESCRIPTION ECN FINISH ELECTRO TIN PLATE DWG. NO. 186-cp4388 UNIT INCH									TITLE	VVIRE							
REVEDATE DWIN CITY DESCRIPTION LON ELECTROTIN PLATE 186-CP4388 INCH 4	00 23	3-Aug-25	Ruby Feng							WROUGHT (COPPER LB)43801A		N	TS		ROJECTION
4 3 / 2 1			DWN	СНК		DESCRI	PTION		ECN FINIS		DWG. NO.	186-cn4:	888 0	NIT		Wt	