								ī									
		4			3			\bigvee	2					11			_
•	THE INFORMATION DISCLOSED IN CO							CELESTR CAT.NO	··	IRE SIZE	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01	
	DISLOSED EXCEP							LB043801A	D_	FLEX							
								251	#4 AWG	105/24 #4 Weld	3/8	1.84	0.62	0.08	1.00	0.33	
_																	_
D	NOTE:		DIMENSION CIFIED.	NS ARE IN IN	CHES UNLES	SE										D	
		LIST	ED BY "UNI	B,WP AND J DERWRITER: S AND FLEX		B											
		OTH		O.WITH "L" H PECIFIED IN		os *s											
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FINISH:	ELE: SPE	CTOR-TIN F	PLATE UNLES TE PER MIL -	SS OTHERWI T -16366.	SE		Beveled wire entry————————————————————————————————————									С
	SUFFIX CAT.NO.WITH "SP" FOR SILVER. — Wire inspection hole																
\rightarrow	INSTALLATION GUIDE DIE CODE = 29						BOLT SIZE										
	DIE COLOR	= Gray						-(G G				Die C	olor		
В		c(N	L) _{US}	√ RoHS	, S					Color co	ded ba	rel ma	arkings				В
		LIST WIRE CON		2002/95/EC													
		ZMVV/2/7:8	.±013913														
		I	<u> </u>	<u> </u>						<u> </u>							
									HU		ELES 76. Hua					_	
									www.huya		Panyu I					11.	
Α							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									Α	
	00 23-Aug-25	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION									
	REV DATE	DWN	CHK			RIPTION		ECN	FINISH ELECTRO TI	DWG NO	301AP-25 186-cp44		INIT	ICH -	()	\exists	
		4				3		<u> </u>	2	WI LAIL	. 50 ор-т-		111	1	Т	-	
		-		I		-	•	T	_			I		•			