			4			3	4	7	~	2				1			
1	DISCL	OSED IN CON	IFIDENCE ANI	D NOT TO BE F	PROERTY OF CELESTRA, REPRODUCED, USED OR	IS		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB023801A-26		150/24 #2 Weld	3/8	1.83	0.68	0.10	1.00	0.41	
D	N	OTE:	1. ALL	DIMENSION	S ARE IN INCHES UNI	ESS OTHERWISE											D
			SPE	CIFIED.						-		3					
			LIST	ED BY "UND	3,WP AND J SERIES O DERWRITERS INC." AN	ID "CSA" FOR USE											
					S AND FLEX/24 STRAM						°*°		Ď				
			OTH).WITH "L" HAS NOT P ECIFIED IN THE SUFF						so So						
	М	IATERIAL:			IVITY WROUGHT COF	PER											
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Beveled wire entry H									С
					WITH "SP" FOR SILVE	ER.											
									_─Wire i	nspection hole	_						
\rightarrow	> INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown																4
														Die C	olor		
В					\checkmark					Color co	ded bar	rel ma	arkinas				в
D			C	Dus	RoHS								anninge				Б
			ZMVV/2/7/6	.E513913													
								I I	HUY								
									www.huyac		76. Hua Panyu (n.	
А								WIRE CONNECTORS AND SOLDERING									A
								LUGS FOR CODE AND FLEX CABLE									
			Ruby Feng	<u> </u>		andards Spec. Initialed	d.		RIAL HIGH-CONDU WROUGHT C	OPPER DB023	801A-26	1	SCALE N	TS -			
	REV	DATE	DWN 4	СНК	DES	CRIPTION 3	/	ECN FINI	ELECTRO TIN	PLATE	186-cp44	39 ⁽	IN	<u>сн</u>	ΨĽ		1
			4		I	J	4		۷.			I		I			