IP: M. NOTIC: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Specified: I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE DIE COLOR - Biown I: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE DIE COLOR - Biown I: ALL DIM		4				3	\checkmark	7		2				1		
Image: Note: 1. ALL DMEMSIONS ARE IN INCHES UNLESS OTHERWISE SpecifieD. 3. ALL DA DELALEWP AND J SERIES OF CAT NO.S ARE USTED BY "UNDERWITTERS INC. MD YESK TOR USE ON GODE WHEE AND FLEXA'S TRANDED CARLS." PRE-FRID. 3. ALL DA DELALEWP AND J SERIES OF CAT NO.S ARE USTED BY "UNDERWITTERS INC. MD YESK TOR USE OTHERWISE SPECIFIED IN THE SUFFIX OF THE CARLS." PRE-FRID. 3. ALL DA DELALEWP AND J SERIES OF CAT NO.S ARE USTED BY "UNDERWITTERS INC. MD YESK TOR USE OTHERWISE SPECIFIED THE SUFFIX OF THE CARLS." PRE-FRID. 4. High CONDUCTIVITY WROUGHT COPPER FINISH: FINISH: ELECTOR TIN PLATE UNLESS OTHERWISE SUFFIX CAT NO.WITH "SP FOR SLUER." INSTALLATION GUIDE DIE CODE = 33 DIE CODE = 33 DIE CODE = 43 DIE CODE = 43 DI	DISCLOSED IN CO	ONFIDENCE ANI	D NOT TO BE F	PROERTY OF CE REPRODUCED, U	ELESTRA, IS JSED OR					1			-	-	-	
SPECIFIED. SPECIFIED. ALL DADB LAL BAY PAND J SERIES OF CAT.NO S ARE LISTED BY VINCERWRITERS INC' AND 'GSA' FOR USE ON CODE WIRES AND FLEXA'S STRANEDE CABLES. PRE-ERV. CAT.NOWITH 'UAS NOT FEED FOILE UNLESS OTHERWISE SPECIFIED IN THE SUPFIX OF THE CAT.NO. WITH 'P. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FNISH: ELECTOR-TIM PLATE INLESS OTHERWISE SPECIFIED PLATE FER. HILL: 'HIGH CONDUCTIVITY WROUGHT COPPER FNISH: ELECTOR-TIM PLATE INLESS OTHERWISE SUFFIX CAT.NO.WITH 'SP' FOR SILVER. WIRE inspection hole DIE COLOR = Brown DIE COLOR = Brown DIE COLOR = Brown DIE COLOR = Brown COLOR COME DIE COLOR = BROWN COLOR COLOR =	DISLOSED EXCER	- I FOR WHICH	TORNISHED.]		LB021458A	#2 AWG	125/24 = 50.5		1.28	0.59	0.11	0.62	0.36
LISTED BY 'UNDERWRITERS INC' AND 'CGA' FOR USE ON COODE WIRES AND FLEXX3 STRANGED CABLES. PRE-FIX CAT.NO.WITH 'L' HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: SECONDE DATE PER HILL - 1:458. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE COLOR = Brown Wire inspection hole BOLT SIZE GUIDE COLOR = Brown INSTALLATION GUIDE DIE COLOR = Brown Color coded barrel markings Color coded barrel markings Color coded barrel markings VITE WWI: huyaco.com MATERIAL: WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE VITE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND SOLDERING LUGS FOR CODE AND SOLDERING LUGS FOR CODE AND FLEX CABLE	NOTE:	SPE	CIFIED.													
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CATINO. WITH "P." D MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL-17-16306. SUFFIX CAT.NO.WITH 'SP'FOR SILVER. INSTALLATION GUIDE DIE COLOR = Brown DIE COLOR = Brown Image: State of the component of t	-	LIST	ED BY "UNE CODE WIRE	DERWRITERS S AND FLEX/2	INC." AND "C 24 STRANDED	SA" FOR USE CABLES.					∍ /I	B				
FINISH: ELECTOR.TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T. 16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown Wire inspection hole Generation of the second seco	MATERIAL	OTH WIT	IERWISE SP H "P".	ECIFIED IN TH	HE SUFFIX OF	THE CAT.NO.					^چ *		Ď			
INSTALLATION GUIDE DIE COLOR = 33 DIE COLOR = Brown BOLT SIZE Image: State of the		ELE SPE	CTOR-TIN P CIFED PLAT	LATE UNLESS E PER MIL - T	S OTHERWISE 7 -16366.			Bevele	ed wire entry	V H						
Image: Second State Standards Spec. Initialed. Material High-Converting Mat	DIE CODE :	= 33						L	Wire	•	Ē					
Distribution Distribution <thdistribution< th=""> Distribution <thd< td=""><td></td><td></td><td>`</td><td>\checkmark</td><td></td><td></td><td></td><td></td><td></td><td>G</td><td></td><td></td><td></td><td></td><td>nolo</td><td></td></thd<></thdistribution<>			`	\checkmark						G					nolo	
0 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER PRT. NO. LB021458A SCALE NTS THRID ANGLE PROJECTION				RoHS 2002/95/EC						Color co	ded ba	rrel ma	arkings		-	
0 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER PRT. NO. B021458A SCALE NTS THRID ANGLE PROJECTION																
OU 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER PRT. NO. LB021458A SCALE ITHID ANGLE PROJECTION											76. Hu	ancun	Rd. Zł	nongci	in Tow	
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. WROUGHT COPPER LB021458A NTS																
REV DATE DWN CHK DESCRIPTION ECN FINISH electro tin plate DWG. NO. 186-cp4442 UNIT INCH			<u> </u>	Се					WROUGHT (COPPER LBC	21458A		N	TS		ROJECTION
4 3 \wedge 2 1			I СНК					FCN FINIS		DWG. NO.	186-cn4/	142 U	INIT		Wt	