	_		4		1		2	7	1		2				1				
	THE	INFORMATION	I ON THIS DRA	WING IS THE	PROFRTY OF	CELESTRA, IS	3		V CELESTRA		2 IRE SIZE	BOLT	В	С	D	G	Н		
	DISC	CLOSED IN CON	VEIDENCE AND	NOT TO BE I					CAT.NO	CODE	FLEX		_	-	±0.015	_	±0.01		
	BioEx	OOLD EXOLIT	TOK WITHOUT	OMMONIED.			_		LB025634A-25	50 #2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil		1.51	0.66	0.10	0.75	0.37		
D		NOTE:		DIMENSION CIFIED.	IS ARE IN I	NCHES UNLES	S OTHERWISE											D	
_			LIST	ED BY "UND	DERWRITE	J SERIES OF C RS INC." AND " X/24 STRANDE	CSA" FOR USE		B										
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								D D									
	1	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
C	;	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H									С	
	[[INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown							—Wire inspection hole —BOLT SIZE									\leftarrow	
В			c (U	D us	RoH 2002/95/9	S					Color cod	ded barre	el mar	rkings	Die ¢c	olor		В	
_			WIRE CONN ZMVV/2/7/8															_	
										HU\ www.huyac		ELES 76. Huar Panyu Di	icun F	Rd. Zh	nongcu	ın Tow			
А									TI	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					ed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID AND WROUGHT COPPER LB025634A-250 NTS							ID ANGLE PE	ROJECTION			
1	REV	DATE	DWN	CHK		DESCR	RIPTION		ECN FII	NISH ELECTRO TIN	DWG NO	186-cp445	O UN		—	(H)	\exists	.	
		•	4				3	Δ	\uparrow	2	·				1			<u> </u>	