Implementation ALL DADBLALE MY ADD SERIES OF CALMS AS BULLESS OTHERWISE Decision Serie Information Decision Serie Information NOTE: 1. ALL DADBLALE WAND SERIES OF CAT MS ARE USTED DY MERCANNERS INC: NO CAM SARE USTED DY MERCANNERS USTED DY MERC			4				3	\forall			2				1		
INDTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFED. 2. ALL DA.BLIALB.WO AND JSERES OF CAT NO.5 ARE LISTED BY UNDERWRITERS INC: AND COAP OR DUSS ON GODE WHEEAND FLACK STRANDED CARLESS PREFIX CAT.NO.WITH'L' HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFED PLATE PER MIL. T-RISGO SPECIFED PLATE PER MIL. T-RISGO	DISCLOSE	ED IN CON	FIDENCE AND	D NOT TO BE	PROERTY O REPRODUCE	F CELESTRA, IS ED, USED OR									_	-	
NOTE: 1. ALL DRENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIC: 2. ALL DADB.LALB.WP AND J SERIES OF CATINDS ARE LISTED BY "UNDERWARTERS INC." AND CSA' FOR USE ON COOL WIRES AND EXPLANSION OF THE CATINDS ARE LISTED BY "UNDERWARTERS INC." AND THE SUFFIX OF THE CATIND. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. T. 16886. SUFFIX CAT. NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE COLOR = Brown DIE COLOR = Brown INSTALLATION GUIDE DIE COLOR = Brown I	DISLOSED	J LXGLFT		I OKNISHED.				LB0	23801A-250	#2 AWG	125/24 = 50.5		1.83	0.66	0.10	1.00	0.37
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "Pr. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MILT. 16306. SUFFIX CAT.NO.WITH "SP" FOR SILVER. INSTALLATION GUDE DIE COLOR = Brown DIE COLOR = Brown Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel markings TIL VILL VILL </td <td></td> <td>E:</td> <td>SPE 2. ALL LIST</td> <td>CIFIED. DA,DB,LA,L ED BY "UNI</td> <td>B,WP AND DERWRITE</td> <td>J SERIES OF C RS INC." AND "(</td> <td>AT.NO.S ARE CSA" FOR USE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>B</td> <td></td> <td></td> <td></td> <td></td>		E:	SPE 2. ALL LIST	CIFIED. DA,DB,LA,L ED BY "UNI	B,WP AND DERWRITE	J SERIES OF C RS INC." AND "(AT.NO.S ARE CSA" FOR USE						B				
SPECIFED PLATE PER ML. T. 16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE COLOR = Brown	MATI	ERIAL:	OTH WITI	IERWISE SF H "P".	PECIFIED II	N THE SUFFIX C	OF THE CAT.NO.					్లి		D			
INSTALLATION GUIDE DIE COLOR = 33 DIE COLOR = Brown INSTALLATION GUIDE DIE COLOR = Brown Color coded barrel markings Celestra Corporation 76. Huancun Rd. Zhongcun Town. 77. Wille Connectores And SoldeRing 171E Wire Connectores And SoldeRing 172E Wire Connectores And SoldeRing 172E Wire Connectores And SoldeRing 172E Wire Connectores And S	FINIS	SH:	SPE	CIFED PLAT	LE PER MII	T -16366.	SE		Bevele	ed wire entry	y H						
Color coded barrel markings CELESTRA CORPORATION COLOR CODE AND COLOR CODE AND FLEX CABLE COLOR CODE AND FLEX CABLE CELESTRA CORPORATION CELESTRA CORPORATION CELESTRA CORPORATION COLOR CODE AND FLEX CABLE CELESTRA CORPORATION CELESTRA CONDUCTIVITY CELESTRA CONDUCTIVITY CELESTRA CORPORATION CELESTRA CONDUCTIVITY CELESTRA CORPORATION CELESTRA CORPORATION CELESTRA CONDUCTIVITY CEL	DIEC	CODE = 3	33						¢								
Image: State of the state				US ED NECTORS LE513913	Rol	IS				-		oded ba	rrel ma	arkings		lor	
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER PRT. NO. LB023801A-250 SCALE NTS THRID ANGLE PROJECTION												76. Hu	ancun	Rd. Zh	nongcu	un Tow	
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. WROUGHT COPPER LB023801A-250 NTS									TITLE	VVIRE							
REV DATE DWN CHK DESCRIPTION ELECTROTIN PLATE WG. NO. 186-cp4452		-Aug-25								WROUGHT C	COPPER LB02	3801A-25	0	N	TS	4	ROJECTION
4 3 2 1						D E O O D	IDTION	l r	EINISH	Н	DWG. NO.	400 -	U	NIT	I - I	n + }} +	