_	,					1								
		4 3		\downarrow	\bigvee 2				1					
ı				ROERTY OF CELESTRA, IS		CELEST	**	VIRE SIZE	BOLT		C D	G	Н	1 '
		CONFIDENCE AN CEPT FOR WHICH		PRODUCED, USED OR		CAT.N	CODE	FLEX	-	MIN ±0	0.04 ±0.01	5 ±0.02	±0.01	1
					<u> </u>	LB021034	AP- #2 AWG	60 Navy #4 Weld 125/24 = 50.5		1.28 0	.60 0.10	0.75	0.37	
						250		kcmil						1
D														D
	NOTE:			ARE IN INCHES UNLE	SS OTHERWISE									
		SPECIFIED.												
					RIES OF CAT.NO.S ARE									
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.							↓					
	1	PRF	F-FIX CAT.NO.\	WITH "L" HAS NOT PEE	P HOLF UNLESS									
		OTH	HERWISE SPE	CIFIED IN THE SUFFIX			S &							
			H "P".											
	MATERIA	L: HIG	H CONDUCTIV	ITY WROUGHT COPP	ΕR									
С	FINISH:			ATE UNLESS OTHERW PER MIL - T -16366.	ISE	D								
				/ITH "SP" FOR SILVER		В	Beveled wire entry——— H							
	INSTALL	INSTALLATION GUIDE					Wire inspection hole							
	DIE CODE = 33					-BOLT SIZE								
	DIE COL	OR = Brown										\vdash		
						-		\$ \frac{1}{2} \frac{1}{2} \frac{1}{2} \frac{1}{2} \fra						
	B													
В								Die	Color		В			
							Color coded barrel markings							
	LISTED 2002/95/eG													
		WIRE CONNECTORS ZMVV/2/7/8.E513813												
														l
								A R C	ELES1	ΓRAC	ORPO	RATI	ON	
							HU		76. Huan					
							www.huya	co.com	Panyu Di	st. Gua	ngzhou (511495.		
Α			+ +			WIRE CONNECTORS AND SO LUGS FOR CODE AND FLEX (SOLDERING			Α
	00 44 Day 05 Duby Fara Ciris Civ						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PR						ROJECTION	
		7 0				501	WROUGH	COPPER LB0210	34AP-250	LINUT	NTS	6 F	\neg	
1	REV DAT		CHK	DESC		ECN	ELECTRO T	IN PLATE	186-cp4456	5 51111	INCH	Ψ ^L		1
		4			3	4	2				,	1		
						1								