			4		1				L		•		1		4			
		4				3	\	<u>/</u>	2		<u> </u>		1				,	
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	F FOR WHICH	FURNISHED.					LB021434AP- 260	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil		1.39	0.60	0.11	0.75	0.36	
D	N	IOTE:		DIMENSION CIFIED.	IS ARE IN I	NCHES UNLES	S OTHERWISE											
			LIST	ED BY "UNI	DERWRITE	J SERIES OF C. RS INC." AND "( X/24 STRANDE	CSA" FOR USE		B d									
			OTH				P HOLE UNLESS OF THE CAT.NO.		So so D									
	М	IATERIAL:	HIGI	H CONDUCT	TIVITY WRO	OUGHT COPPE												
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H									С
-	D	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown								Wire inspection hole  BOLT SIZE								
В			c U	<b>D</b> us	RoH 2002/95/	S					Color cod	ded barre	el maı	rkings-	Die Col	dor		В
_			WIRE CON ZMVV/2/7/8															_
									HUYA® Www.huyaco.com  CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α									TIT	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MA	MATERIAL HIGH-CONDUCTIVITY PRT. NO.  WROUGHT COPPER LB021434AP-260 NTS							ROJECTION		
ı	REV		DWN	СНК		DESCR	IPTION		ECN FIN		DWG NO	186-cp4478	LIN		<b></b>   4	$\bigoplus $ $\in$	$\exists$	
			4				3			2			İ		1			
									•									