			4				3		\downarrow			2				1				
I	DISCLOS	ED IN CON	FIDENCE AND	NOT TO BE		F CELESTRA, IS D, USED OR	6			LESTRA AT.NO	WI CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLOSE	D EXCEPT	FOR WHICH I	FURNISHED.						21401AP- 260	#2 AWG	60 Navy #4 We 125/24 = 50.5 kcmil	ld	1.64	0.60	0.11	1.00	0.36		
D	NOT	TE:		DIMENSION CIFIED.	NS ARE IN I	NCHES UNLE	ESS OTHER	RWISE												
			LIST	ED BY "UNI	DERWRITE	J SERIES OF RS INC." ANE X/24 STRANI	D "CSA" FOF	FOR USE												
			OTH			HAS NOT PE NTHE SUFFIX		D D												
	MAT	TERIAL:	HIGH	H CONDUC	TIVITY WRO	DUGHT COPF	PER													
С	FINI	ISH:	SPE	CIFED PLA	TE PER MIL	ESS OTHERV T -16366. ' FOR SILVEF			Beveled wire entry										С	
\rightarrow		TALLATIC CODE = 3								Wire inspection hole BOLT SIZE										
В		COLOR =		Dus	Rot	/ IS,				¢			coded ba	rrel ma	rkings	Die Çol	lor		В	
					2002/95										intings					
																			—	
											HUY ww.huyac		CELES 76. Hui Panyu	ancun	Rd. Zh	nongcu	in Tow			
A										ITTLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
			Ruby Feng			Celestra Star					RIAL HIGH-CONDU WROUGHT C	OPPER LB02	1401AP-20	50	CALE N	TS THRI				
I	REV	DATE	DWN	СНК		DESC	CRIPTION			CN FINIS	ELECTRO TIN	I PLATE	186-cp44	179 U	^{NIT} IN	СН (1	Ψt		l I	
			4				3		4		2									