			4		ı		0		7		0				4				
		4 3 NFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS		3	*		2			<u> </u>					,				
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE					CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB023878AP- 260	#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil		1.71	0.60	0.11	0.88	0.36		
D	N	IOTE:		DIMENSION CIFIED.	NS ARE IN I	NCHES UNLES	S OTHERWISE	,											
			LIST	ED BY "UNI	DERWRITE	J SERIES OF C RS INC." AND "(X/24 STRANDE		B											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								D D										
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H									С	
\rightarrow	INSTALLATION GUIDE DIE CODE = 33								—Wire inspection hole —BOLT SIZE										
D		IE COLOR :				,					e din H				Die Co	plor			
В			C LIST		RoH 2002/96/	S					Color cod	ded barr	el ma	rkings				В	
																		_	
								HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
Α										- TITLE WIRE CONNECTORS AND SOLDERING A								А	
									LUGS FOR CODE AND FLEX CA										
	00							WROUGHT COPPER LB023878AP-260 NTS						RID ANGLE PI	ROJECTION	ECTION			
1	REV	DATE	DWN	CHK		DESCR	IPTION		ECN FINI	SH ELECTRO TIN	N PLATE DWG. NO.	86-cp448	2 1	IN:	сн 📗	⊕ Ł	\exists		
			4				3	4		2					1				