	4			3			$\overline{\}$	2				1						
'	DISCL	OSED IN CON	ON THIS DRA	NOT TO BE		F CELESTRA, IS ED, USED OR			CELESTR/ CAT.NO	A V CODE	/IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
D	DISLO	SED EXCEPT	FOR WHICH I	-URNISHED.					DB015678A-2		75 Navy #2 Wel 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	5/16	1.63	0.70	0.11	0.88	0.42	D
	N	OTE:		DIMENSION CIFIED.	IS ARE IN I	NCHES UNLE	SS OTHERWISE											
			LIST	ED BY "UNI	DERWRITE		CAT.NO.S ARE "CSA" FOR USE DED CABLES.											
			OTH				EP HOLE UNLES OF THE CAT.NC											
		ATERIAL:										ૢૢૢૢૢૢૢૢૢૢ૾૾ૼ૾ૺ		_				
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							C									С	
	Beveled wire entry																	
\rightarrow		ISTALLATIC									inspection hole							\leftarrow
		IE COLOR =							-BOLT SIZE									
В					V	/					exim _H							В
_			C	JUS	Rol-	IS ■9					−G−⇒				Die Co	olor		-
	LISTED WHE CONNECTORS ZMVV/2/7/B_E513913									Color coded barrel markings								
												CELES				οΔτιά		
										HU		76. Hua	ancun	Rd. Zh	nongcu	ın Towi		
А										www.huyaco.com Panyu Dist. Guangzhou 51149								А
									LUGS FOR CODE AND FLEX CABLE									
			Ruby Feng				dards Spec. Initial	led.		MATERIAL HIGH-CONI WROUGHT	COPPER DB01	5678A-25	0		TS		OJECTION	
	REV	DATE	DWN	СНК		DESC	RIPTION	/	ECN F	ELECTRO T	DWG. NO.	186-cp44	.96 U	init IN	СН ¹ 1	ΨĽ		
			4				3	L		2					1			