			4			3			:	2				1			
1	DISCL	OSED IN CON	IFIDENCE ANI	D NOT TO BE I	PROERTY OF CELESTR REPRODUCED, USED O			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB011458A-2	251 #1 AWG	225/24 #1 Weld	1/4	1.33	0.76	0.12	0.62	0.46	
D	N	IOTE:	1. ALL	DIMENSION	IS ARE IN INCHES U	NLESS OTHERWIS	SE .										D
				CIFIED.			_				⊲[3	4				
			LIST	ED BY "UNE	B,WP AND J SERIES DERWRITERS INC." / S AND FLEX/24 STR	AND "CSA" FOR US											
					D.WITH "L" HAS NOT		-ss										—
			OTH		ECIFIED IN THE SU						oj-						
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER							Beveled wire entry									
С	F	INISH:	ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.														С
					.WITH "SP" FOR SIL												
								Wire inspection hole BOLT SIZE									
\rightarrow	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green																+
										-G>				Die C	Color		
В				2	\checkmark					Color co	oded ba	rel ma	arkings				В
			C	Pus	RoHS												
			LIS WIRE CONF ZMVV/2/7/8														
		1															
									HUY		CELES 76. Hua						
^								<u> </u>	www.huyac	o.com	Panyu I	Dist. G	Guangz	hou 5	11495.		А
А									WIRE CONNECTORS AND SOLDERING								
		00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					tial ad	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION									
	00 Rev		Ruby Feng	CHK		Standards Spec. Init	liaied.			DWG. NO.	1458A-25 186-cp45	_	INIT IN	CH .	(\square	
		1	4	<u> </u>		3	Ĺ		2				114	1			
								I									