			4			3		\downarrow		2				1			
1	DISCL	OSED IN CON	FIDENCE ANI	D NOT TO BE F	PROERTY OF CELESTF REPRODUCED, USED C			CELESTI CAT.NO		WIRE SIZE	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB011458A		225/24 #1 Wel	d 1/4	1.26	0.75	0.12	0.62	0.45	
_																	_
D	N	OTE:			S ARE IN INCHES L	INLESS OTHER	WISE										D
			_		B,WP AND J SERIES		ADE	B →									
			LIST	ED BY "UND	DERWRITERS INC." S AND FLEX/24 STF	AND "CSA" FOF	RUSE										
					D.WITH "L" HAS NOT			D D									—
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									2						
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER							Beveled wire entry									
С	F	INISH:	SPE	CIFED PLAT	LATE UNLESS OTH E PER MIL - T -1636 .WITH "SP" FOR SIL	6.				"'⊸H ⊶							С
									/ Wire	e inspection hol	e						
\sim	 INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green 																\triangleleft
															Color		
_					./				×	⊢G–⊶ Color (oded ba	rrol ma	arkinga				_
В			C()	L)US	RoHS						oueu ba		arkings				В
				TED	Evelouico												
			ZMVV/2/7/8														
																	—
									HU								
									www.huya		76. Hua Panyu						
А								WIRE CONNECTORS AND SOLDERING									А
								LUGS FOR CODE AND FLEX CABLE									
		-	Ruby Feng	<u> </u>		Standards Spec			MATERIAL HIGH-CON WROUGH FINISH	IDUCTIVITY PRT. NO. T COPPER DB0 DWG. NO.	11458A-26	1	INIT	TS .	RID ANGLE PF		
	REV	DATE	DWN 4	СНК		ESCRIPTION 3		ECN	ELECTRO ⁻		186-cp48	510 ⁶	IN	<u>сн</u> 1	ΨĽ		
			4		Ι	5		4	2			I		I			