		4	1				3	\downarrow		2	2				1				
'	DISCLOSE	IN CONFIDEN	CE AND NOT	TO BE REPRO	RTY OF CELESTRA, DUCED, USED OR	IS			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	'	
D	DISLOSED	EXCEPT FOR \	VHICH FURN	ISHED.				L	_B011243A		75 Navy #2 We 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	d	3.00	0.88	0.11	1.75	0.41	D	
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																		
	ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									B V									
С	FINIS		ELECTOI SPECIFE	R-TIN PLATE D PLATE PE	WROUGHT COF UNLESS OTHER R MIL - T -16366. I "SP" FOR SILVE		Beveled wire entry												
\rightarrow	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green								Wire inspection hole —BOLT SIZE										
В	CULUS ROHS LISTED WHEE CONHECTORS								Color coded barrel markings										
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
А									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. OATE DWN CHK DESCRIPTION					MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER LB011243A SCALE NTS ECN FINISH DWG. NO. 196 en 1520 UNIT NACH							ANGLE PE	PROJECTION				
	REV D		WN 0 1	CHK	DES		3	4	ECN F	ELECTRO TIN	I PLATE	186-cp45	20 0	IN	1 1	Ψ ^L			