		4			3	$\downarrow$		2				1			
1	DISCLOSED	N CONFIDENCE AN	ID NOT TO BE RE	ROERTY OF CELESTRA, EPRODUCED, USED OR	IS	CELEST CAT.N		IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	'
D	DISLOSED E	(CEPT FOR WHICH	FURNISHED.			LB011434/	0022	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223			0.70	0.11	0.75	0.42	D
J	NOTE:	SP	ECIFIED.	S ARE IN INCHES UN											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.														
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".														
<b>C</b>	MATER FINISH			VITY WROUGHT CO ATE UNLESS OTHER		Beveled wire entry H									
С		SP		E PER MIL - T -16366 WITH "SP" FOR SILV	В										
	INSTALLATION GUIDE DIE CODE = DIE COLOR =					_	Wire inspection hole  BOLT SIZE								<del></del>
В		C U	US TED INECTORS NECTORS	RoHS 2002/95/EC		Color coded barrel markings									
		Lavva	To had take to												
							HU\ www.huyac		ELES 76. Huar Panyu Di	icun R	Rd. Zh	ongcu	n Towr		
Α							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00 04-Ma	y-25 Ruby Fenç	Sinia Qiu	Celestra St	andards Spec. Initialed	i.	WROUGHT COPPER LB011434A-250 NTS						ANGLE PR	OJECTION	
1	REV DA		CHK	DES	SCRIPTION	ECN	FINISH ELECTRO TIN	DWG. NO.	186-cp4522	2 UN	IN (	CH   `	<b>9</b> E		1 1
		4			3	4	2					1			