		4			3	3	7	2					1	1	
DISC		FIDENCE ANI	d not to be f	PROERTY OF CELEST REPRODUCED, USED			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01
			TONNISHED.				LB015634A-250) #1 AWG	75 Navy #2 Welc 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	5/16	1.51	0.70	0.11	0.75	0.42
1	NOTE:		DIMENSION CIFIED.	S ARE IN INCHES	UNLESS OTHERWI	SE									
		LIST	FED BY "UND	ERWRITERS INC.	S OF CAT.NO.S AR " AND "CSA" FOR U RANDED CABLES.				ŀ	⇒F	3	-2			
		OTH			DT PEEP HOLE UNL UFFIX OF THE CAT.						-				
	MATERIAL:			IVITY WROUGHT						so _x o		U			
	FINISH:	SPE	CIFED PLAT	LATE UNLESS OTI E PER MIL - T -163 WITH "SP" FOR SI	366.		Bevele	Beveled wire entry							
[[INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green						/Wire inspection hole								
3		C		RoHS			¢							olor	
_			NECTORS BE513913	-					Color co	ded ba	rrel ma	arkings]		
										CELES 76. Hua Panyu I	ancun	Rd. Zh	nongci	un Tow	
							TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
00	23-Aug-25	Ruby Feng	Sinia Qiu CHK		a Standards Spec. In	itialed.	ECN FINIS	ERIAL HIGH-COND WROUGHT (COPPER LB01	634A-25	2	CALE N	ts		
REV	DATE				DESCRIPTION				PLATE	186-cp45					