	_																	
			4				3	\bigvee	2					1			.	
•		INFORMATION				CELESTRA, IS D. USED OR			CELESTRA	-	RE SIZE	BOLT	В	C	D .0.015	G	H	·
		OSED EXCEPT				_,		-	CAT.NO	CODE	FLEX 75 Navy #2 Weld	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	}
								L	.B013801A-25	0 #1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil	3/8	1.83	0.70	0.11	1.00	0.42	
											133/.0223							D
		NOTE:		DIMENSION CIFIED.	IS ARE IN II	NCHES UNLESS	OTHERWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
_	1												 —					
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
C	7	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.																С
			SUF	FIX CAT.NO).WITH "SP"	FOR SILVER.			Raya	led wire entr								
									Beveled wire entry————————————————————————————————————									
	_	INSTALLATION GUIDE DIE CODE = 37							/—Wire inspection hole									\leftarrow
		DIE CODE = 37 DIE COLOR = Green								/ BOLT SIZE								
									2			-						
									(F)		\$ C							
В	3																	В
L		CUL US ROHS						Color coded barrel markings]	
		WIF ZM	.ISTED RE CONNECTORS VV/2/7/8.E513913		,						Color co	ded bari	rei ma	rkings	i — /			
_																		
												FLFS	TRΔ	CO	RPOI	RATIO	NC	1
															A CORPORATION n Rd. Zhongcun Town.			
											nyu Dist. Guangzhou 511495.							
Δ	\vdash								WIRE CONNECTORS AND SOLDERING									Α
										LUGS FOR CODE AND FLEX CABLE								
	00	00 28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION									
	RE\		DWN	CHK		DESCRI			ECN FIN	WROUGHT C	DWG NO	801A-250		NIT	TS -	6 E	7	
	IXE.	/ DAIL	4	CHIN	ı	DLOCKI	3	\wedge		ELECTRO TIN	PLATE	186-cp452	G	IN	ICH 1	Ψ -	7	J
	_		4		I		3	4	7	Z					I			