			4				3			2					1			
1	DISCLOS	ED IN CON	FIDENCE AND	NOT TO BE F	PROERTY OF C REPRODUCED,			CELEST CAT.N	_ —	WIRE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	Ì '
D	DISLOSEI	D EXCEPT	FOR WHICH F	-URNISHED.				LB011434.		75	5 Navy #2 Weld 150/24 = 60.5 ccmil 175/24 = 70.6 kcmil 133/.0223	1/4	1.39	0.75	0.10	0.75	0.41	D
	NOT	ΓE:	 ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE 															
			LIST ON (PRE-	ED BY "UND CODE WIRES -FIX CAT.NC	ERWRITERS S AND FLEX/ D.WITH "L" H/	INC." AND "(24 STRANDE AS NOT PEEF	CSA" FOR USE		B									
	МАТ	ΓERIAL:	WITH	H "P".		GHT COPPEI						g ^{xo}		D				
С	FINI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry														С		
	DIE	TALLATIO CODE = 3 COLOR =	37				Wire inspection hole BOLT SIZE											
В			C UI	US ED ECIDES	RoHS 2002/95/eC			Color coded barrel markings										
			ZMVV/2/7:8.	E513913														_
										JY huyaco.d	\mathbf{A}°	ELES 76. Hua Panyu D	ncun	Rd. Zh	nongcu	ın Tow		
Α	A TITLE WIRE CONNECTORS LUGS FOR CODE AN														А			
	\vdash							WROUGHT COPPER LB011434A-260 NTS							ID ANGLE PE	OJECTION		
	REV	DATE	DWN 4	CHK	<u> </u>	DESCR	3	ECN	ELE	CTRO TIN PLA	TE DWG. NO.	186-cp453	35 0	IN	1 1	Ψ -	7	J