	•																		
		4				3			abla	2							1		_
ļ				WING IS THE D NOT TO BE F		F CELESTRA, IS			CELESTR		WIRE	SIZE	BOLT	В	С	D	G	Н	1 '
			T FOR WHICH		REPRODUCE	D, USED OR			CAT.NO		DDE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	l
									LB015601 <i>A</i>	NP- #1 /	AWG 2	225/24 #1 Weld	5/16	1.76	0.76	0.12	1.00	0.46	l
										'	'					-!-			
D																			D
	N	NOTE:			S ARE IN I	NCHES UNLES	SS OTHERWISE	Ē											l
				CIFIED.			ED OF OAT NO C ARE												
							RIES OF CAT.NO.S ARE NC." AND "CSA" FOR USE												l
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.						-											
			PRE	FFIX CAT.NO	D.WITH "L"	HAS NOT PEEP HOLE UNLESS													
				IERWISE SP H "P".	ECIFIED IN	THE SUFFIX	OF THE CAT.NO	0.		-90,									
						OUGHT COPPE													l
		//ATERIAL:																	
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry H										
						FOR SILVER.													
																			l
								/—Wire inspection hole											
\rightarrow	INSTALLATION GUIDE							BOLT SIZE											
		DIE CODE = 37 DIE COLOR = Green									\leftarrow			1					
			OLOR = Green																
D		⊸-G								>				Die	COLOR		В		
В		c(UL)US .RoHS.							Color coded barrel markings										
			- 110:		2002/95/	ĒC													
			WIRE CON																
			280 012776																
_	ł																		_
												A 0 1		TD 4			DATI	ON	
										HI	JY	A [®]	CELES 76. Hua					_	
											nuyaco.		Panyu l						
Α										TITLE WIRE CONNECTORS AND SOLDERING								Α	
									WIRE CONNECTORS AND SOL							KING			
								LUGS FOR CODE AND FLEX CABLE											
	00	23-Aug-25	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				aled.	WROUGHT COPPER LB015601AP-251 NTS							_	ROJECTION			
ı	REV	DATE	DWN	CHK		DESCI	RIPTION		ECN	FINISH ELE	CTRO TIN PL	ATE DWG. NO.	186-cp45	45	nit In	ICH	(\exists	
		4 3							\triangle		2					1			
	•				•									•					