			4				3		7		2				1			
•			ON THIS DRA NFIDENCE ANI			CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB011401AF	<u>, </u>								
									261	#1 AWG	225/24 #1 Weld	1/4	1.64	0.75	0.12	1.00	0.45	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	IS ADE IN I	NCHES UNLESS	CTHERWISE											D
	"	IOTE.		CIFIED.	NO ARL IN I	NOTIES UNLES	OTTILKWISL											
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							→ B →									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.									S D							—	
	WITH "P".																	
	M	MATERIAL:	HIG	H CONDUC	TIVITY WRO	OUGHT COPPER	2											
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTI SPECIFED PLATE PER MIL - T -163						E	y	_						С			
						FOR SILVER.		20.11.02										
										Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
		DIE CODE = 37 DIE COLOR = Green																
		()																
															Dia	alor		
В		⊢—G—⊶									Die Colo							
Ь	· (II)								Color coded barrel markings—								В	
	C US ROHS																	
		WIE ZM	.ISTED RE CONNECTORS VV/2/7/8.E513813		•													
	1																	
												ELES	TRA	CO	RPO	RATIO	ON	
										76. Huancun Rd. Zhongcun Town.							_	
										www.huyaco.com		Panyu Dist. Guangzhou 511495.						
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								Α
									+									
	00	28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO WROUGHT COPPER LB011401AP-261 NTS							ROJECTION			
	REV		DWN	CHK		DESCRI		-	ECN F	NISH ELECTRO TII	DWG NO	186-cp45		INIIT	ICH	(\exists	
			4		I		3	/	<u> </u>	2	TI EATE	. 30 30 10		111	1	T	_	
			•		I		-	_	Γ'	-			I		•			