	,		4		ı		2	+		0		1		4		
	THEIN	VIEODMATION	4	WING IC THE	DDOEDTY OF	OFLECTRA IC	3			2	1			1 -		,
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		CELESTRA, IS D, USED OR		CELES CAT.I		WIRE SIZE FLEX	BOLT SIZE	B   MIN   ±	C D 0.04 ±0.01	G 5 ±0.02	H ±0.01	ĺ
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB10143		100 Navy #1 We	eld 1/4		0.75 0.12		0.45	
D	N	IOTE:		DIMENSION CIFIED.	NS ARE IN IN	NCHES UNLESS	S OTHERWISE					•	·			D
			LIST	ED BY "UNI	DERWRITER	J SERIES OF CARS INC." AND "C K/24 STRANDE	CSA" FOR USE		B							
			OTH				HOLE UNLESS F THE CAT.NO.		D D							
	M	MATERIAL:	HIGI	H CONDUCT	TIVITY WRO	UGHT COPPER	₹									
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H							
-	D	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink							Wire inspection hole  BOLT SIZE							
В			c <b>(U</b>	<b>D</b> us	RoH: 2002/95/E	S.				Color o	oded barr	el mark	ings—	Çolor		В
_			WIRE CONF													
										YACO.com		ncun Ro	CORPC d. Zhongo angzhou	cun Tow		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							
	00	23-Aug-25	3-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID AND WROUGHT COPPER DB101434A-260 NTS						ROJECTION	
	REV	DATE	DWN	СНК		DESCRI	IPTION	ECN	FINISH	D TIN PLATE DWG. NO.	186-cp456	4 UNIT		<b>+</b> E	$\exists$	
			4				3	$\triangle$	2	'				1		