			4				3	\downarrow	7		2				1			
I	DISCL	OSED IN CON	VFIDENCE AN	d not to be i	PROERTY OF CELES REPRODUCED, USEI				CELESTRA CAT.NO	CODE WI	IRE SIZE	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				ſ	DB105601A-261		275/24 1/0 Wel		1.70	0.83	0.12	1.00	0.50	
_																		_
D	N	IOTE:			S ARE IN INCHES	S UNLESS OT	THERWISE											D
			-		B WP AND J SERI				B d									
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 																
			OTH		D.WITH "L" HAS N ECIFIED IN THE \$		D D											
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								Povolod wire entry									
С	F	INISH:	SPE	CIFED PLAT	LATE UNLESS OT TE PER MIL - T -16 .WITH "SP" FOR \$	6366.			Beveled wire entry									
										Wire i	inspection hole							
\rightarrow	IN	NSTALLATIO	ON GUIDE														\triangleleft	
		IE CODE = IE COLOR =							- C						Die Ci	olor		
В					\checkmark					·		oded bai	rrel ma	arkinas				В
Б			ငပျ	D us	Rohs													Б
			ZM/V/2/7/	8.E513913														
		1	1															
										HUY	R	CELES 76. Hua						
•										vww.huyac		Panyu l						
A									WIRE CONNECTORS AND SOLDERING									A
		00.405			0.1		0		MAT		UCTIVITY PRT. NO.		S	CALE	ТНЕ	RID ANGLE PF	ROJECTION	
	00 Rev	23-Aug-25 DATE	DWN	CHK		DESCRIPT	Spec. Initialed.		ECN FINI	WROUGHT (DWG, NO,	5601A-26 186-cp45	_	INIT IN	CH -	(\square	
	L	1	4	<u> </u>		3		4		2			-	11 N	1	1		
								I										