IP-IN-DUBMAIC DOI: IN-BURNING BIT - BURNING         Decousing includes and provide and includes understanding and provide and pro			4				3	$\checkmark$	7		2				1		
LESCORD EX.E.* FOR MILLENOMBORS         NOTE:       1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE         SPECIFIED.       2. ALL DADELALE, WP AND J SERIES OF CAT NO.S ARE UNITED BY "UNDERWRITERS INC: "AND "CAT NO WHIT "L' HAS NOT PEEP FOLE UNLESS ON CODE WIRES AND FLEXAZES TRANSIDE DATE."         MATERIAL:       HIGH CONDUCTIVITY WROUGHT COPPER         PRE-FIX CAT NO WITH "L' HAS NOT PEEP FOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P:         MATERIAL:       HIGH CONDUCTIVITY WROUGHT COPPER         FINISH:       ELECTOR TIM PLATE OLICESS OTHERWISE SPECIFIED PLATE PER MIL. 1 - 1:0506 SUFFIX CAT.NO.WITH "SP" FOR SILVER.         MISTALLATION GUIDE DIE CODE = 42 DIE CODE = 42 DIE CODE = 42 DIE COLOR - Prink       Wire inspection hole BOUT SIZE Color coded barrel markings         Color coded barrel markings       CelEESTRA CORPORATION 76. Huancun Rd. Zbongoun Town. Pmu Dist. Guagzhou 51149:S.         WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE       WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE         0.       23-Jug 28. Ruby Fing Sink Qu       Celestin Standards Spec. Initiaed.       WIRE MILLENCOMENT       Sint Qu	DISCLOSE	ED IN CON	FIDENCE ANI	D NOT TO BE I	PROERTY OF	E CELESTRA, IS D, USED OR					1			-	-	-	
SPECIFIED.  a. ALL DA DB LAL BWY AND J SERIES OF CAT NO S ARE LISTED DE 'UNDERWRITER'S INC' AND 'CSA' FOR USE ON CODE WIRES AND FLEXA'S STRANDED CABLES. PRE-FIX CAT NOW TH' 'UN'NO THE FOR THE CAT.NO. WITH 'P. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINSH: ELECTOR-TIM PLATE INLESS OTHERWISE SPECIFIED PLATE FER HILL - T. 1630 SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE CODE + 42 DIE COLOR = Pink  INSTALLATION GUIDE DIE COLOR = PINK  I	DISLOSED	JEXCEPT	FOR WHICH	FURNISHED.					LB101401A		100 Navy #1 Weld 225/24 = 90.8		1.88	0.75	0.13	1.00	0.46
2. ALL DA.DB.LALB.WP AND J SERIES OF CAT.NO S ARE LISTED BY 'UNDERWRITERS INC.' AND 'CSA' FOR USE ON COOD WRIES AND FEEP HOLE UNLESS OTHERWSE SECIFIC IN THE JUNES OF THE CAT.NO. WITH 'P. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINSH: ELECTOR TIN PLATE UNLESS OTHERWISE SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUDE DE COLOR = Pink WIRe inspection hole DE COLOR = Pink INSTALLATION GUDE DE COLOR = Pink Color coded barrel markings Color coded barrel markings Color coded barrel markings TABLE CONDUCTIVE REAL OF THE CALL O	NOTE	E:			IS ARE IN I	NCHES UNLESS	OTHERWISE										
MATERIAL:       HIGH CONDUCTIVITY WROUGHT COPPER         FINISH:       ELECTOR-TIN PLATE UNLESS OTHERWISE         SPECIFED PLATE PER MIL-7-16366.       SUFFIX CAT.NO.WITH 'SP' FOR SILVER.         INSTALLATION GUDE       DIE COLOR = Pink         INSTALLATION GUDE       BOLT SIZE         DIE COLOR = Pink       BOLT SIZE         INSTALLATION GUDE       Color coded barrel markings         Color coded barrel markings       Color coded barrel markings         Color coded barrel markings       Color coded barrel markings         INSTALLATION GUDE       INSTALLATION GUDE         DIE COLOR = Pink       INSTALLATION GUDE         INSTALLATION GUDE       INSTALLATION GUDE         DIE COLOR = Pink       INSTALLATION GUDE         INSTALLATION GUDE       INSTALLATION GUDE         DIE COLOR = Pink       INSTALLATION GUDE         INSTALLATION GUDE       INSTALLATION GUDE	-		2. ALL LIST ON ( PRE OTH	DA,DB,LA,L ED BY "UNI CODE WIRE FIX CAT.NO IERWISE SP	DERWRITE S AND FLE D.WITH "L"	RS INC." AND "C X/24 STRANDEI HAS NOT PEEP	CSA" FOR USE D CABLES. HOLE UNLESS					<u>الم</u>	B				
SPECIFED PLATE PER ML - T. 16366.         SUFFIX CAT.NO.WITH "SP" FOR SILVER.         INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink         DIE COLOR = Pink         INSTALLATION GUIDE DIE COLOR = Nink         INSTALLATION GUIDE DIE COLOR = Pink         INSTALLATION GUIDE DIE COLOR = Nink         INSTALLATION GUIDE DIE COLOR = Pink         INSTALLATION GUIDE DIE COLOR = Nink         INSTALLATION GUIDE DIE COLOR = Pink         INSTALLATION GUIDE DIE COLOR = Nink	MATE	ERIAL:			TIVITY WRO	OUGHT COPPER	R					5-					
INSTALLATION GUIDE DIE COLOR = 42 DIE COLOR = Pink       BOLT SIZE         Image: Second and the second a	FINIS	SH:	SPE	CIFED PLAT	TE PER MIL	T -16366.	E		Bevele	ed wire entr	y H						
DIE COLOR = Pink									/	Wire i	•	Ξ					
Elestra Corporation     Celestra Corporat	DIE C	COLOR =		DUS	RoH	S			¢		-	ded ba	rrel ma	arkings		nor	
0       23-Aug-25       Ruby Feng       Sinia Qiu       Celestra Standards Spec. Initialed.       MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER       PRT. NO. BI01401A       SCALE NTS       THRID ANGLE PROJECTION	-																
00     23-Aug-25     Ruby Feng     Sinia Qiu     Celestra Standards Spec. Initialed.     MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER     PRT. NO. UB101401A     SCALE NTS     THRID ANGLE PROJECTION												76. Hu	ancun	Rd. Zł	nongci	in Tow	
00     23-Aug-25     Ruby Feng     Sinia Qiu     Celestra Standards Spec. Initialed.     WROUGHT COPPER     LB101401A     NTS									TITLE	VVIRE							
REV DATE DWN CHK DESCRIPTION ECN FINISH ELECTRO TIN PLATE DWG. NO. 186-cp4580 UNIT INCH		-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed.		MATE		COPPER LB1	01401A	S	CALE N	TS	RID ANGLE PR	
	00 23-,								ECN FINIS	H	DWG. NO.	400 40		INIT		((+)) +−	-+