THE BROWNE CAN USE THE STREPT OF CLEATER, B         Decided in the Strept of the BROWNE CAN USE OF BROWNE STREPT OF CLEATER, B         Decided in the Strept of the BROWNE CAN USE OF BROWNE STREPT OF CLEATER, B         Decided in the Strept of the BROWNE CAN USE OF BROWNE STREPT OF CLEATER, B         Decided in the Strept of the BROWNE CAN USE OF BROWNE STREPT OF CLEATER, B         Decided in the Strept of the BROWNE CAN USE OF BROWNE STREPT OF CLEATER, B         Decided in the Strept of the BROWNE STREPT OF CLEATER, B         Decide Strept of the Strept of CAN TAB ST	- 	4			3	$\forall$		2				1		
Document 2005       Document 2005<	DISCLOSED IN CON	VFIDENCE AND N	NOT TO BE REPRO	RTY OF CELESTRA, IS DUCED, USED OR							-	-	-	
NOTE:       1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE         SPECIFIED.       2. ALL DADBLALB.WP AND J SERIES OF CAT NO S ARE LISTED BY "UNDERWINTERS INC: AND COSA' FON USE ON COCOUNTIES AND COSA' FON USE ON COCOUNTIES AND COSA' FON USE OTHERWISES SPECIFIED IN THE SUFFIX OF THE CAT NO. WITH 'P'.         MATERIAL:       HIGH CONDUCTIVITY WROUGHT COPPER FINISH:       ELECTOR: TIM PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. T. 16386.         SUFFIX CAT NO WITH 'SP' FOR SILVER.       Wire inspection hole         DIE COLOR = Pink       Wire inspection hole         DIE COLOR = Pink       Color coded barrel markings         Color coded barrel markings       Celestra CorpOpartion         MATERIAL:       HULL Y: AND WITH 'SP' FOR SILVER.         WWW.NUYACO.COM       Celestra CorpOpartion         MATERIAL:       WIRE CONNECTORS AND SOLDERING         UNIT ALL TION GUIDE       USE SPECIFIED PLATE PER MIL. T. 16386.         DIE COLOR = Pink       WIRE inspection hole         DIE COLOR = Pink       WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND SOLDERING         DIE COLOR = Pink       WIRE CONNECTORS AND SOLDERING         DIE COLOR = Pink       WIRE CONNECTORS AND SOLDERING         DIE COLOR = Pink <td>DISLOSED EXCEPT</td> <td>FOR WHICH FO</td> <td>RNISHED.</td> <td></td> <td></td> <td>LB101458A-2</td> <td></td> <td>100 Navy #1 Welc 225/24 = 90.8</td> <td></td> <td>1.33</td> <td>0.76</td> <td>0.12</td> <td>0.63</td> <td>0.46</td>	DISLOSED EXCEPT	FOR WHICH FO	RNISHED.			LB101458A-2		100 Navy #1 Welc 225/24 = 90.8		1.33	0.76	0.12	0.63	0.46
ON CODE WREE AND FLEX/24 STRANDED CABLES.         PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS         OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.         WITH "P".         MATERIAL:       HIGH CONDUCTIVITY WROUGHT COPPER         FINISH:       Elector Thi NUATE UNLESS OTHERWISE         SUFFIX CAT.NO.WITH "SP" FOR SILVER.         INSTALLATION GUIDE         DIE COLOR = Pink         INSTALLATION GUIDE         DIE COLOR = Pink         OTHERWISE         INSTALLATION GUIDE         DIE COLOR = Pink         INSTALLATION GUIDE         INSTALLATION GUI		SPECII 2. ALL DA	FIED. A,DB,LA,LB,WP	AND J SERIES OF C	AT.NO.S ARE			F	J	8	-4			
FINISH:       ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - 1 - 45866. SUFFIX CAT NO.WITH 'SP' FOR SILVER.         INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink       Wire inspection hole Good = 42 DIE COLOR = Pink         INSTALLATION GUIDE DIE COLOR = Pink       Image: Color coded barrel markings         INSTALLATION GUIDE DIE COLOR = Pink       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color coded barrel markings       Image: Color coded barrel markings         Image: Color code code code code code code code code		ON CO PRE-FI OTHEF	DE WIRES AND IX CAT.NO.WIT RWISE SPECIFI	D FLEX/24 STRANDE	D CABLES. HOLE UNLESS				۰ بار م <sup>عد</sup> م					
INSTALLATION GUIDE DIE COLOR = Pink		ELECT SPECII	OR-TIN PLATE	UNLESS OTHERWIS R MIL - T -16366.		Beve	eled wire entr	y H						
Color coded barrel markings  Color coded barrel markings  Color coded barrel markings  Celestra component of the component of	DIE CODE = 4	42					Wire	•	Ξ					
0       23-Aug-25       Ruby Feng       Sinia Qiu       Celestra Standards Spec. Initialed.       MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER       PRT. NO. LB101458A-250       SCALE NTS       THRID ANGLE PROJECTION				RoHS				-	ded ba	rrel ma	arkings	Die ¢c	nolor	
www.huyaco.com     Panyu Dist. Guangzhou 511495.       www.huyaco.com     Panyu Dist. Guangzhou 511495.       www.huyaco.com     Panyu Dist. Guangzhou 511495.       understand     UILE       www.huyaco.com     Panyu Dist. Guangzhou 511495.       understand     WIRE CONNECTORS AND SOLDERING       understand     Waterial High-conductivity       www.huyaco.com     NTS       understand     Waterial High-conductivity       www.huyaco.com     NTS														
00     23-Aug-25     Ruby Feng     Sinia Qiu     Celestra Standards Spec. Initialed.     MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER     PRT. NO. LB101458A-250     SCALE NTS     THRID ANGLE PROJECTION														n.
00     23-Aug-25     Ruby Feng     Sinia Qiu     Celestra Standards Spec. Initialed.     WROUGHT COPPER     LB101458A-250     NTS					LUGS FOR CODE AND FLEX CABLE									
REV     DATE     DWN     CHK     DESCRIPTION     ECN     FINISH     ELECTRO TIN PLATE     DWG. NO.     186-cp4587     UNIT     INCH     INCH	00 23-Aug-25	Ruby Feng S	Sinia Qiu	Celestra Standa	rds Spec. Initialed.		WROUGHT COPPER LB101458A-250 NTS							
			СНК	DESCR	IPTION	ECN FI		DWG. NO.	186-cp45	587 0	INIT		Wt	