			4				3	$\downarrow$	2	2				1			
I	DISCL	OSED IN COM		D NOT TO BE F	PROERTY OF CELE REPRODUCED, USE			CELESTRA CAT.NO	WIRE CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
-						]		LA4012P-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/4	3.02	1.08	1.02	1.94	0.56	
D	N	OTE:		DIMENSION CIFIED.	S ARE IN INCHE	S UNLESS	OTHERWISE	Color coded marking Bolt Size									D
					3,WP AND J SEF DERWRITERS IN												
	ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
			OTH	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													
0		IATERIAL: INISH:	_		IVITY WROUGH												
С			SPE	CIFED PLAT	E PER MIL - T -1 WITH "SP" FOR	6366.				<u>B</u>	-						С
								-		Α	-						
$\rightarrow$	D	ISTALLATIO	54														$\triangleleft$
		IE COLOR =	= Purple					]-	R	Inspect	on Hol	е		1			
В																	в
D		¢ل	)us 📍	i N	EBS	RoHS		ΤĘ					E	ļ			
		LISTE WIRE CONN	D						Bevele	d entry							
									-								
A								HUY	CORPORATION								
										Panyu Dist. Guangzhou 511495.							
									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
		-	Ruby Feng	<u>                                     </u>	Celes		ds Spec. Initialed.		MATERIAL HIGH-CONDU WROUGHT CO	OPPER LA40	LA4012P-260 NTS						
	REV	DATE	DWN	СНК		DESCRIP		ECN	FINISH ELECTRO TIN	PLATE DWG. NO.	186-cp04	59 <sup>U</sup>	NIT IN		O E		l
	_ 4   3						პ	4	2					ľ			