DBSL28DL BACKHORMSHEL CATINO CODE TEEX NIN 6.04 40015 6.002 ±x NOTE: 1. ALL DAMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFICD 2. ALL DA BLALEWE AND JERIES OF CATINO SARE UB105001A.250 100 AWG 0.075 0.12 1.00 0 NOTE: 1. ALL DA BLALEWE AND JERIES OTHERWISE SPECIFICD 0.12 1.00 0 INTERIAL: HIGH CONDUCTIVITY WOUGHT COMPERENCE: AND CARLESS THE WIFE KINC: AND CARLESS THE WIFE KINC: AND CONDUCTIVITY WOUGHT COMPERE FINISH: ELECTOR: TH PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL: T- 10000 SUFFIX CAT NO. WITH ''HAS NOT PEEP HOLE UNLESS MATERIAL: HIGH CONDUCTIVITY WOUGHT COMPERE BEVEIGED PLATE PER MIL: T- 10000 Beveided wire entry- H. INSTALLATION CUIDE DE COLOR = Pink EGOE SUFFIX CAT NO. WITH ''HAS NOT PER MIL: T- 100000 Color coded barrel markings INSTALLATION CUIDE DE COLOR = Pink EGOE Color coded barrel markings INSTALLATION CUIDE EGOE EGOE EGOE EGOE IDE COLOR = Pink EGOE EGOE EGOE EGOE EGOE I		4			3	2			1					
LICEGED BLOCH FOR WHICH PUBLICATED NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFICD 2. ALL DADBLALB WE AND USERIES OF CATING SARE ON CODE WHICH AND THE SUFFICIENT OF THE CATING WHICH PUBLICATING WHICH SPECIFIED IN THE SUFFICIENT OF THE CATING WHICH PUBLICATING WHICH SPECIFIED IN THE SUFFICIENT OF THE CATING WHICH PUBLICATING WHICH SPECIFIED IN THE SUFFICIENT OF THE CATING SUFFIX CAT NO WITH 'SP' FOR SILVER. INSTALLATION CUIDE DE CODE # 42 DIE COLOR = Pink SUFFIX CAT NO WITH 'SP' FOR SILVER. INSTALLATION CUIDE DIE COLOR = Pink Image: Suffix CAT NO WITH 'SP' FOR SILVER. INSTALLATION CUIDE DIE COLOR = Pink Image: Suffix CAT NO WITH 'SP' FOR SILVER. INSTALLATION CUIDE DIE COLOR = Pink Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suffix CAT NO WITH 'SP' FOR SILVER. Image: Suf	DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR											-	-	H ±0.0
SPECIFIED. ALL DADLALEN WAND J SERIES OF CATINO.S ARE LISTED BY "UNDERWRITERS INC". AND CCA" FOR USE ON CODE WIRES AND FLEXAS STRANDED CABLES. PRE-EX CATINO.WITH 'L'HAS NOT PEEP HOLE UNLESS OTHERWIGE SPECIFIED IN THE SUFFIX OF THE CATINO. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIM PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. 'T-16866. SUFFIX CATINO.WITH'S' FOR SILVER. WITH 'P'. MATERIAL: MIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIM PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. 'T-16866. SUFFIX CATINO.WITH'S' FOR SILVER. WITH 'P'. MINISTALLATION GUIDE DIE COLOR = Pink WITH 'P'. WITH 'P'. MINISTALLATION GUIDE DIE COLOR = Pink WITH 'P'. MINISTALLATION GUIDE DIE COLOR = Pink MINISTALLATION GUIDE DIE COLOR = Pink MINISTALLATION GUIDE DIE COLOR = NON. MINISTALLATION GUIDE	DISLOSED EXCEPT	FOR WHICH FOR	RNISHED.			LB105601		100 Navy #1 Wel 225/24 = 90.8		1.76	0.76	0.12	1.00	0.46
LISTED BY 'UNDERWRITERS NC' AND 'CSA' FOR USE ON CODE WIRES AND FERZAZ STRANDED CABLES OTHERWISE SPECIFIED IN THE SUFFIX OF THE CATNO. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PERMIL - 1-1656 SUFFIX CATNO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE COLOR = Pink INSTALLATION GUIDE DIE COLOR = Pink Color coded barrel markings Color coded barrel markings Color coded barrel markings Color coded barrel markings COLOR CODE AL2 DIE COLOR = DIALE DE COLOR =	NOTE:	SPECIF	FIED.											
Interpretention of the on t	-	LISTED ON CO PRE-FI	BY "UNDERW DE WIRES AN X CAT.NO.WIT	/RITERS INC." AND "(D FLEX/24 STRANDE "H "L" HAS NOT PEEF	CSA" FOR USE D CABLES. P HOLE UNLESS			+	⇒ 	3				
SPECIFED PLATE PER ML - T - 16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink DIE CODE = 42 DIE COLOR = Pink INSTALLATION GUIDE DIE COLOR = Pink INSTALLATIO	MATERIAL:	WITH "I	P".						ŵ¢ [°]		D			
INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink Image: State of the	FINISH:	SPECIF	ED PLATE PE	R MIL - T -16366.	SE	В	eveled wire entr	ry H						
Image: Second	DIE CODE = 4	42					Wire	•	Ē					
LISED LISED NUMCOTALE DIMENT CELESTRA CORPORATION NUMCOTALE DIMENT FILL HIGH CONNECTORS AND SOLDERING NUMCOTALE DIMENT TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE	DIE COLOR =	= Pink		\checkmark								Die ço	olor	
Image: State of the state				ROHS				Color co	ded ba	rrel ma	arkings			
Image: State of the state							1							
WIRE CONNECTORS AND SOLDERING UUGS FOR CODE AND FLEX CABLE MATERIAL HIGH-CONDUCTIVITY PRT. NO.									76. Hua	ancun	Rd. Zł	nongcu	in Towi	
						LUGS FOR CODE AND FLEX CABLE								
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. WROUGHT COPPER LB105601A-250 NTS	00 23-Aug-25	Ruby Feng S	Sinia Qiu	Celestra Standa	ards Spec. Initialed.		WROUGHT COPPER LB105601A-250 NTS							
REV DATE DWN CHK DESCRIPTION ECN FINISH ELECTRO TIN PLATE DWG. NO. 186-cp4590 UNIT INCH	REV DATE	DWN	СНК	DESCR	IPTION	ECN	FINISH ELECTRO TI	N PLATE	186-cp45	590 ^L	INIT	ICH	Ψt	