					_			T										
		4		3			2			1								
'					PROERTY OF REPRODUCED	CELESTRA, IS D. USED OR			CELESTRA CAT.NO		IRE SIZE	BOLT SIZE	B MIN	C	D	G	H ±0.01	i '
			FOR WHICH				_	-	CAT.NO	CODE	FLEX 100 Navy #1 Weld		IVIIIN	±0.04	±0.015	±0.02	±0.01	ł
								lι	LB103801A-25	1/0 AWG	225/24 = 90.8		1.83	0.76	0.12	1.00	0.46	
								L			kcmil 133/.0254							
D	l																	D
	l N	IOTE:		DIMENSION CIFIED.	IS ARE IN IN	NCHES UNLESS	SOTHERWISE											
		<ol> <li>ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>																
									B									
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								9	- 90° ½								
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE																
					TE PER MIL D.WITH "SP"	- T -16366. FOR SILVER.		Beveled wire entry————————————————————————————————————									С	
_		INSTALLATION GUIDE							Wire inspection hole									
	D	DIE CODE = 42							BOLT SIZE									
	ں	DIE COLOR = Pink																
															Die Co	ulor		
В		CUL)US ROHS							Color coded barrel markings—									В
		L	.ISTED	2002/95/EC	l													
			RE CONNECTORS VV/2/7/8.E513813															
																		l —
	<u> </u>	ı	ı						1 1									
								ļl I			ELES							
٨										HUYA® 76. Huancun Rd. Zhongcun Town. www.huyaco.com Panyu Dist. Guangzhou 511495.							n.	
																		_
Α										WIRE CONNECTORS AND SOLDERING								A
										LUGS FOR CODE AND FLEX CABLE								
	00	14-Dec-25	4-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MA	TERIAL HIGH-COND WROUGHT		801A-250	SC	CALE NT		ID ANGLE PF	ROJECTION	
	REV	DATE	DWN	CHK		DESCRI	PTION		ECN FIN	ELECTRO TI	N PLATE DWG. NO.	186-cp459	1 U	IN IN	CH +	(H)	$\exists$	
	4   3							4		2	İ		Ī		1			·
					'			l					'					