	•					1											
		4 3		\downarrow	\bigvee 2				1								
ı				ROERTY OF CELESTRA, IS		CELEST	** -	/IRE SIZE	BOLT	В	С	D	G	Н	1 '		
		XCEPT FOR WHICH		PRODUCED, USED OR		CAT.N	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	1		
						LB103801	AP- 1/0 AWG	100 Navy #1 Weld 225/24 = 90.8	3/8	1.83	0.76	0.12	1.00	0.46			
						250		kcmil 133/.0254							1		
D															D		
	NOTE:			ARE IN INCHES UNLE	SS OTHERWISE												
		SPECIFIED.															
					RIES OF CAT.NO.S ARE												
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	1	PR	F-FIX CAT.NO.\	WITH "L" HAS NOT PEE	P HOLF UNLESS										—		
		ОТ	HERWISE SPE	CIFIED IN THE SUFFIX		Č Š											
			ΓΗ "P".														
	MATER	IAL: HIC	SH CONDUCTIV	ITY WROUGHT COPP	≣R												
С	FINISH			ATE UNLESS OTHERW PER MIL - T -16366.	D	Beveled wire entry H											
				/ITH "SP" FOR SILVER	D												
	INSTAI	INSTALLATION GUIDE					Wire inspection hole										
	DIE CO	DE = 42	_				BOLT SIZE										
	DIE COLOR = Pink							\leftarrow	_								
												Dia	alor				
В) Die Co	SION		В						
	c(UL)US JROHS,						Color coded barrel markings										
	LISTED																
		WIRE CONNECTORS ZMVV/2/7/8.E513813															
															l		
								<u> </u>									
									ELES	TRA	COI	RPO	RATIO	NC			
							HU		76. Hua					n.			
_			 				www.huya	co.com	Panyu D	ist. G	uangz	:hou 5	11495.				
Α			+ +			TITLE WIRE CONNECTORS AND SOL						DEF	RING	A			
			+ +			LUGS FOR CODE AND FLEX CA					ABL	E					
	00 46 5	16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION										
						WROUGHT COPPER LB103801AP-250 NTS							⊕ +	7			
	NLV DA		CHK	nesc			ELECTRO T	N PLATE	186-cp459	1	IN	CH	P		1		
		4		l	3	4	2					1					
						•											