			4				3			:	2		1		1			
1	DISCLC	SED IN CON		D NOT TO BE	PROERTY OF CE REPRODUCED, U				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	'
	DIGLOG						]		LB101201AP- 250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/2	2.10	0.80	0.12	1.00	0.46	
D	NC	DTE:		DIMENSION CIFIED.	NS ARE IN INCH	HES UNLESS	OTHERWISE											D
			LIST	ED BY "UNI	.B,WP AND J S DERWRITERS S AND FLEX/2	INC." AND "C	SA" FOR USE		B B									
			OTH		O.WITH "L" HAS PECIFIED IN TH			D D										
	MA	ATERIAL:	HIG	H CONDUC	TIVITY WROUG	GHT COPPER												
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry								
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink								-Wire inspection hole BOLT SIZE								$\leftarrow$	
В				DUS	RoHS				K		G	ded bai	rel ma	urkings	Die Ço	lor		В
			WIRE CON ZMVV/2/78															_
										HUY www.huyad			ancun	Rd. Zł	nongcu	<b>RATIC</b> In Towi 11495.		
A									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									A
			Ruby Feng		Cel		ds Spec. Initialed.			TERIAL HIGH-CONDI WROUGHT (	COPPER LB1012	01AP-25	0	CALE N	TS THR	ID ANGLE PR		
	REV	DATE	DWN 4	СНК		DESCRI	PTION 3			electro tin	I PLATE	86-cp45	99	nit IN	<u>сн</u> 1	ΨT		l