DISLOSED EXCEPT FOR WHICH FORNISHED.			4				3	$\forall$			2				1		
1000000 D.N.C.   100 Navy et Weid   12   2.83   0.81   0.11   1.75   0.44     NOTE:   1. ALL DMENSIONS ARE IN INCHES UNLESS OTHERWISE   SPECIFIED.   2.   ALL D.A.D.BLALB WP AND JSERIES OF CAT NO S ARE ON USE ON CODE WRITERS INC: AND 'COA'FOR USE ON CODE WRITERS PRECIPIED NITE'S UPLICA STRADED CALLESS   PRE-FIX CAT NO WITH 'L' HAS NOT 'CEAF FOR MISE ON CODE PRE FINISH:   ELECTOR-TIM PLATE UNLESS OTHERWISE SPECIFIED NITE'S UPLICA STRADED CALLES.     MATERIAL:   HIGH CONDUCTIVITY WROUGHT COPPER   FINISH:   ELECTOR-TIM PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. T-16566.     SUFFIX CAT NO WITH 'L' HAS NOT PEEP HOLE UNLESS   OTHERWISE SPECIFIED PLATE PER MIL. T-16566.   SUFFIX CAT NO WITH 'L' HAS NOT PEEP HOLE UNLESS     MATERIAL:   HIGH CONDUCTIVITY WROUGHT COPPER   ENDITIONAL TO MALE THE PER MIL. T-16566.   SUFFIX CAT NO WITH 'L' HAS NOT PEEP HOLE UNLESS     MITH 'L' HIGH CONDUCTIVITY WROUGHT COPPER   ENDITION PLATE PER MIL. T-16566.   SUFFIX CAT NO WITH 'L' HAS NOT PEEP HOLE UNLESS   Eveled wire entry   Color coded barrel markings     INSTALLATION GUIDE   DIE COLOR - PINK   Color coded barrel markings   Color coded barrel markings     INSTALLATION JULIE   EVENT HUGH STALES SOURCESS SOURCESS OTHERWISE   EVENT HUGH SOURCESSOURC	DISCL	OSED IN COM	FIDENCE ANI	D NOT TO BE	PROERTY O REPRODUCE	F CELESTRA, IS D, USED OR									_	-	H ±0.0
SPECIFIED.     9. ALL DADBLARM PARD J SERIES OF CAT NO S ARE LISTED BY "UNDERWRITERS INC: AND "CSA" FOR USE ON CODE WIRES AND FLEXAS STRANDED CABLES.     PREFERV CAT NO.WITH 'I HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH 'P'.     MATERIAL:   HIGH CONDUCTIVITY WROUGHT COPPER     FINISH:   ELECTOR TIM PLATE INLESS OTHERWISE SUFFIX CAT.NO.WITH 'SP' FOR SILVER.     INSTALLATION GUIDE DIE COOL = 42 DIE COLOR = Pink   Wire Inspection hole BOLT SIZE DIE COLOR = Pink     INSTALLATION GUIDE DIE COLOR = Pink   Color coded barrel markings     INSTALLATION GUIDE DIE COLOR = Pink   Color coded barrel markings     INSTALLATION GUIDE DIE COLOR = Pink   INSTALLATION GUIDE DIE COLOR = Pink     INSTALLATION GUIDE DIE COLOR = Pink   INSTALLATION GUIDE DIE COLOR = Pink     INSTALLATION GUIDE DIE COLOR = Pink   INSTALLATION GUIDE DIE COLOR = Pink     INSTALLATION GUIDE DIE COLOR = Pink   INSTALLATION GUIDE DIE COLOR = Pink     INSTALLATION GUIDE DIE COLOR = 2000 COLOR = Pink   INSTALLATION GUIDE DIE COLOR = COLOR = PINK     INSTALLATION GUIDE DIE COLOR = 2000 COLOR = PINK   INSTALLATION GUIDE DIE COLOR = CO	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				LB	101243A-260		100 Navy #1 We 225/24 = 90.8	1/2	2.83	0.81	0.11	1.75	0.45
USTED BY 'UNDERWRITERS INC, 'ND 'CSA' FOR USE ON CODE WRES AND CEXA'S TRANSPEC CABLES.     PRE-FIX CAT.NO.WITH 'L' HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH 'P'.     MATERIAL:   HIGH CONDUCTIVITY WROUGHT COPPER FINISH:     ELECTOR-TIN PLATE UNLESS OTHERWISE SUFFIX CAT.NO.WITH 'SP' FOR SILVER.     INSTALLATION GUIDE DIE CODE + 20 DIE COLOR = Pink     INSTALLATION GUIDE DIE COLOR = Pink	N	OTE:	SPE	CIFIED.	-												
MATERIAL:   HIGH CONDUCTIVITY WROUGHT COPPER     FINISH:   ELECTOR-TIN PLATE UNLESS OTHERWISE     SPECIFED PLATE PER ML - T - 16386.   SUFFIX CAT.NO.WITH "SP" FOR SILVER.     INSTALLATION GUIDE   Beveled wire entry     DIE CODE = 42   DIE COLOR = Pink     INSTALLATION GUIDE   Beveled wire inspection hole     DIE COLOR = Pink   FOR SILVER.     INSTALLATION GUIDE   Beveled wire inspection hole     DIE COLOR = Pink   FOR SILVER.     INSTALLATION GUIDE   Beveled wire inspection hole     DIE COLOR = Pink   FOR SILVER.     INSTALLATION GUIDE   Beveled wire entry     INSTALLATION GUIDE   Beveled wire inspection hole     DIE COLOR = Pink   FOR SILVER.     INSTALLATION GUIDE   Beveled wire entry     INSTALLATION GUIDE   Bourde for color coded barrel markings     Color coded barrel markings   Color coded barrel markings     INSTALLATION GUIDE   INSTALLATION GUIDE     INSTALATION GUIDE	-		LIST ON ( PRE	ED BY "UNI CODE WIRE	DERWRITE S AND FLE D.WITH "L"	RS INC." AND "C X/24 STRANDEI HAS NOT PEEP	CSA" FOR USE D CABLES. HOLE UNLESS						3				
SPECIFED PLATE PER ML - T. 16366. SUFFIX CAT.NO.WITH 'SP' FOR SILVER.   Beveled wire entry   H     INSTALLATION GUIDE DIE COLOR = 42 DIE COLOR = Pink   Wire inspection hole GUIT SIZE Color coded barrel markings     INSTALLATION GUIDE DIE COLOR = 42 DIE COLOR = Pink   Image: Color coded barrel markings     Image: Color coded barrel markings   Color coded barrel markings     Image: Color coded barrel markings   Color coded barrel markings     Image: Color coded barrel markings   Celestra Conport Conport Non. Pay Dist. Guangzhou 511495.     Image: Color coded barrel markings   Title     Image: Color coded barrel markings   Title     Image: Color coded barrel markings   Celestra Conport Non. Pay Dist. Guangzhou 511495.     Image: Color coded barrel markings   Title     Image: Color coded barrel markings   Title Color coded barrel markings	м	IATERIAL:				OUGHT COPPER	R					ୢୖୖୖ					
INSTALLATION GUIDE DIE COLOR = 42 DIE COLOR = Pink   BOLT SIZE     Image: State of the	FI	INISH:	SPE	CIFED PLAT	TE PER MIL	T -16366.	E		Bevele	d wire entry	H H						
Image: Construction of the standards Spec. Initialed.   Image: Construction of the standards Spec. Initialed.   Image: Construction of the standards Spec. Initialed.     Image: Construction of the standards Spec. Initialed.   Image: Constandardsten standards Spec. Initialed. <td< td=""><td>D</td><td>IE CODE =</td><td>42</td><td></td><td></td><td></td><td></td><td></td><td>/</td><td>Wire i</td><td>•</td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	D	IE CODE =	42						/	Wire i	•						
Strength   Strength     Image: Strength   Image: Strength     Imag	DI	IE COLOR :	■ Pink	2	V	/			<pre></pre>						Die Ço	olor	
00   23-Aug-25   Ruby Feng   Sinia Qiu   Celestra Standards Spec. Initialed.   MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER   PRT. NO.   SCALE   NTS   THRID ANGLE PROJECTION				LECTORS LESTIGHTS	Rol- 2002/95/	S					Color co	oded ba	rrel ma	ırkings			
00   23-Aug-25   Ruby Feng   Sinia Qiu   Celestra Standards Spec. Initialed.   MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER   PRT. NO.   SCALE   NTS   THRID ANGLE PROJECTION	·	1	1														
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER PRT. NO. LB101243A-260 SCALE NTS THRID ANGLE PROJECTION												76. Hua	ancun	Rd. Zh	nongci	un Tow	
00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.									TITLE	VVIRE							
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed.		MATE		COPPER LB10	1243A-26	0	N	TS	$\leftarrow$	
		DATE	DWN	СНК		DESCRI	PTION	T	ECN FINISH		DWG. NO.	186-cp46	501 U	NIT IN	сн] -	₩t	