	-	4 3		3	2			1									
I	DISCL	OSED IN CON	FIDENCE ANI	D NOT TO BE I	PROERTY OF CELESTRA, REPRODUCED, USED OR	IS		LESTRA CAT.NO		RE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.)3801A-260	1/0 AWG	100 Navy #1 Wel 225/24 = 90.8 kcmil 133/.0254		1.83	0.75	0.12	1.00	0.45	
D		IOTE:		DIMENSION	IS ARE IN INCHES UN	LESS OTHERWISE					·	-					D
_	-		LIST ON PRE OTF	ED BY "UNE CODE WIRE FIX CAT.NO	B,WP AND J SERIES (DERWRITERS INC." AI S AND FLEX/24 STRA D.WITH "L" HAS NOT F ECIFIED IN THE SUFF	ND "CSA" FOR USE NDED CABLES. PEEP HOLE UNLESS											
	M	IATERIAL:		H "P". H CONDUCI	IVITY WROUGHT CO	PPER					80						
С		'INISH:	SPE	CIFED PLAT	LATE UNLESS OTHEF TE PER MIL - T -16366 .WITH "SP" FOR SILVI		Beveled wire entry										
	D	NSTALLATIO DIE CODE = - DIE COLOR =	42				Wire inspection hole BOLT SIZE										
В			c (Dus	RoHS			- C		G Color co	ded bar	rrel ma	ırkings		nolo		В
									HUY ww.huyac	A	FELES 76. Hua Panyu (ancun	Rd. Zh	nongci	in Tow		
A								ITTLE WIRE CONNECTORS AND SOLDERING A LUGS FOR CODE AND FLEX CABLE A									
		23-Aug-25				andards Spec. Initialed			RIAL HIGH-CONDU WROUGHT C	OPPER LB10	801A-260	<u> </u>	CALE NT	TS -	id angle pr		
	REV	DATE	DWN 4	СНК	DES	SCRIPTION 3	L E	CN FINISH	electro tin	PLATE	186-cp46	04 ⁰	IN	сн	ΨĽ		
	-				I	·	\uparrow					I					