			4				3		7	:	2		1		1			
I	DISCL	OSED IN CON		D NOT TO BE	PROERTY OF CE REPRODUCED, U				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	'
	DIGLO]		LB101401AP- 260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/4	1.64	0.75	0.12	1.00	0.45	
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INC	HES UNLESS	OTHERWISE											D
			LIST	ED BY "UNI	.B,WP AND J S DERWRITERS S AND FLEX/2	INC." AND "C	SA" FOR USE		B defined and the second secon									
			OTH		O.WITH "L" HA PECIFIED IN TH			D D										
		IATERIAL:			TIVITY WROUG													
С	FI	INISH:	SPE	CIFED PLA	PLATE UNLESS TE PER MIL - T D.WITH "SP" FC	-16366.		Beveled wire entry									С	
\rightarrow	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink								Wire inspection hole BOLT SIZE									\leftarrow
В				DUS	RoHS 2002/95/EC	l			-C		G	ded ba	rrel ma	arkings	Die Ç	olo		В
			WIRE CON ZMVV/2/78															_
												76. Hua	ancun	Rd. Zł		RATIC un Towi 11495.		
A									TITLE WIRE CONNECTORS AND SOLDERING A LUGS FOR CODE AND FLEX CABLE A									A
			Ruby Feng		Се		ds Spec. Initialed.			TERIAL HIGH-CONDI WROUGHT (OPPER LB1014	01AP-26	50		TS THR			
	REV	DATE	DWN 4	СНК		DESCRI	3	Ĺ		ELECTRO TIN	IPLATE	186-cp46	510 U	init IN	існ – 1	ΨŢ		