THE INFORMATION ON THIS DRAWING IS THE PROPRIET OF CELESTRA. IS DROCKOSED IN CONTIDENCE AND MOT TO BE REPRODUCED, USED OR DISCLOSED EXCEPT FOR WHICH FURNISHED. 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DADBLALB, WP, ALAS AND J SERIES OF CAT.NO. SARE LISTED BY TUNDERWRITERS INC.* AND "CSA" FOR USE ON CODE WIRES AND FLEXZA STRANDED CABLES. PRE-FIX CAT.NO. WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink DIE COLOR = Pink						
DISCOSED EXCEPT FOR WHICH FURNISHED. CATINO CODE FLEX SIZE MIN 20.04 20.015 20.02 20.01 LB108601AP- 260 LB108601AP- 26						
DISLOSED EXCEPT FOR WHICH FURNISHED. LB10S6014P- 1/0 AWG 100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254 5/16 1.70 0.75 0.12 1.00 0.45 LB10S6014P- 1/0 AWG 225/24 = 90.8 kcmil 133/.0254 5/16 1.70 0.75 0.12 1.00 0.45 D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA.DB.LA.LB.W.P.AL.AS AND J SERIES OF CAT.N.O. SARE LISTED BY 'UNDERWRITERS INC." AND 'CSA' FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.N.O.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.N.O. WITH 'P'. MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL. '1 -16396. SUFFIX CAT.NO.WITH 'SP' FOR SILVER. Wire inspection hole DISTALLATION GUIDE DIE COOLE = 42 DIE COLOR = Plnik D SUFFIX CAT.NO.WITH 'SP' FOR SILVER.	ı					
D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED 2. ALL DA, DB, ILA, LB, WP, AL, AS AND J SERIES OF CAT, NO. S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT NO, WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT, NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. "T -16366. SUFFIX CAT, NO, WITH "SP" FOR SILVER. Wire inspection hole BOLT SIZE DIE CODE = 42 DIE COLOR = Pink						
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MILT -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. NISTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink Wire inspection hole BOLT SIZE						
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL -T16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole BOLT SIZE DIE COLOR = Pink						
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL -T16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole BOLT SIZE DIE COLOR = Pink	D					
2. ALL DA, DB, LA, LB, WP, AL, AS AND J SERIES OF CAT. NO. S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WRES AND FLEX/24 STRANDED CABLES. PRE-IX CAT. NO. WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT. NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL. 1-16386. SUFFIX CAT. NO. WITH "SP" FOR SILVER. Beveled wire entry H Wire inspection hole DIE CODE = 42 DIE COLOR = Pink Wire inspection hole						
LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole BOLT SIZE DIE COLOR = Pink						
ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole BOLT SIZE DIE COLOR = Pink						
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry H Wire inspection hole BOLT SIZE DIE COLOR = Pink						
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry H Wire inspection hole BOLT SIZE DIE COLOR = Pink						
MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T - 16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole BOLT SIZE DIE COLOR = Pink						
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry Wire inspection hole BOLT SIZE DIE COLOR = Pink Beveled wire entry H						
SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry H Wire inspection hole BOLT SIZE DIE COLOR = Pink Beveled wire entry H						
SUFFIX CAT.NO.WITH "SP" FOR SILVER. Wire inspection hole DIE CODE = 42 DIE COLOR = Pink Wire inspection hole	С					
INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink						
INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink						
INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink						
DIE CODE = 42 DIE COLOR = Pink	4					
	<u> </u>					
Diecoto						
Die color						
B	В					
c(UL)us RoHs						
LISTED						
WIRE CONNECTORS ZMrV/Z7/TB_E513613						
HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.						
www.huyaco.com Panyu Dist. Guangzhou 511495.	^					
A TITLE WIRE CONNECTORS AND SOLDERING	Α					
LUGS FOR CODE AND FLEX CABLE						
00 14-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB105601AP-260 NTS THRID ANGLE PROJECTION NTS						
REV DATE DWN CHK DESCRIPTION ECN FINISH ELECTRO TIN PLATE DWG. NO. 186-cp4612 UNIT INCH						
4 1 2						