

THE INFORMATION ON THIS DRAWING IS THE PROPERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED EXCEPT FOR WHICH FURNISHED.

| CELESTRA CAT.NO | WIRE SIZE | | BOLT SIZE | B MIN | C ±0.04 | D ±0.015 | G ±0.02 | H ±0.01 |
|--------------------|-----------|--|--------------|----------|------------|-------------|------------|------------|
| | CODE | FLEX | | | | | | |
| LB103843AP-260 | 1/0 AWG | 100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254 | 3/8 | 2.58 | 0.75 | 0.12 | 1.75 | 0.45 |

D NOTE:



1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.

PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".

MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER

FINISH: ELECTRO-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.

INSTALLATION GUIDE
DIE CODE = 42
DIE COLOR = Pink



Color coded barrel markings



| | | | | | |
|-----|-----------|-----------|-----------|-------------------------------------|-----|
| 00 | 13-Feb-26 | Ruby Feng | Sinia Qiu | Celestra Standards Spec. Initiated. | ECN |
| REV | DATE | DWN | CHK | DESCRIPTION | ECN |

| | | | | | | | | |
|----------|----------------------------------|--|----------|--|--|-------|------|------------------------|
| TITLE | | | | WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE | | | A | |
| MATERIAL | HIGH-CONDUCTIVITY WROUGHT COPPER | | PRT. NO. | LB103843AP-260 | | SCALE | NTS | THIRD ANGLE PROJECTION |
| FINISH | ELECTRO TIN PLATE | | DWG. NO. | 186-cp4614 | | UNIT | INCH | |