	_		_		1		•	_	<u></u>				I					
			4 3 FORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS		\	<u>/</u>	2					1	<u> </u>		.			
	DI	ISCLOSED IN CON	NFIDENCE AND	NOT TO BE I					CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	Di	ISLOSED EXCEPT	FOR WHICH	FURNISHED.					LB103843AP		100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254		2.58	0.75	0.12	1.75	0.45	
[NOTE:		DIMENSION CIFIED.	IS ARE IN II	NCHES UNLES	S OTHERWISE											D
			LIST	DA,DB,LA,L ED BY "UNI CODE WIRE	DERWRITER		B											
_			OTH			HAS NOT PEEF THE SUFFIX (98° \$5										
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
(FINISH:	INISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H								
	>	INSTALLATION GUIDE DIE CODE = 42 DIE COLOR = Pink							Wire inspection hole BOLT SIZE									\leftarrow
E	3		c (U	D us	RoH 2002/95/E	S					Color coo	ded barr	el maı	rkings	Die Co	olor		В
-			WIRE CONN ZMVV/2/7/8															_
										HU\ www.huyac		ELES 76. Huar Panyu D	ncun F	Rd. Zh	ongcu	ın Tow		
F									Tit	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	C	00 23-Aug-25	Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE WROUGHT COPPER LB103843AP-260 NTS							ID ANGLE PE	ROJECTION	
1	RI	EV DATE	DWN	CHK		DESCR	RIPTION		ECN FIN	IISH ELECTRO TII	DWG NO	86-cp461	LIN		—	(H)		
		_	4				3			2					1			·