			1		1		3	7	7		2		1		1			
						CELESTRA, IS	<u> </u>		V CELESTRA		IRE SIZE	BOLT	В	С	Тр	G	Н	
			NFIDENCE AND F FOR WHICH		REPRODUCE	D, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	_		±0.02	±0.01	
							_		LB103801AF 261	1/0 AWG	275/24 1/0 Weld	3/8	1.83	0.83	0.12	1.00	0.48	
															1	1	1	
D																		D
	N	IOTE:		DIMENSION CIFIED.	NS ARE IN I	NCHES UNLESS	OTHERWISE											
					B.WP AND	J SERIES OF C		→ B → →										
		<ol> <li>ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>																
	ł																	—
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								D D								
		WITH "P".																
	M	MATERIAL:	HIGI	H CONDUC	TIVITY WRO	OUGHT COPPER	₹											
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry									С
						FOR SILVER.												
		INSTALLATION GUIDE DIE CODE = 42								Wire inspection hole								
$\rightarrow$										BOLT SIZE								
		DIE COLOR :							(A									
									A		<b>±</b>							
										<b>→</b>	G_=				Die	Color		
В		Color coded barrel markings										В						
		C US ROHS								Color coded barrer markings—								
			LIST WIRE CON	FED JECTORS														
			ZMVV/2/7/8															
	1																	—
		I	I						<u> </u>		- 4 - 0		TD			DATI	ON	
									+	HU)		ELES						
									76. Huancun Rd. Zhongcun T www.huyaco.com Panyu Dist. Guangzhou 51149									
Α									TITLE WIRE CONNECTORS AND SOLDERING A								Α	
		23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							LUGS FOR CODE AND FLEX CABLE									
	00							M	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJE WROUGHT COPPER LB103801AP-261 NTS							ROJECTION		
	REV		DWN	CHK		DESCR		•	ECN FI	NISH ELECTRO TII	DWG NO	186-cp46		INIIT	ICH	<b>(1)</b>	$\exists$	
			4				3	/	<u> </u>	2			<u> </u>	111	1		-	
			-		ı		-		Γ	_			1					