	,							T.										
		4			3			2					1			_		
•					PROERTY OF REPRODUCED	CELESTRA, IS LUSED OR			CELESTRA CAT.NO		IRE SIZE	BOLT SIZE	B MIN	C	D	G	H	i '
			FOR WHICH						CAT.NO	CODE	FLEX 125 NavyN 1/0	SIZE	IVIIN	±0.04	±0.015	±0.02	±0.01	
								DE	B201434A-250	2/0 AWG	Weld 275/24 = 111	1/4	1.53	0.85	0.13	0.75	0.52	
											kcmil 133/.0282							1
D																		D
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN IN	ICHES UNLESS	OTHERWISE											
						050150 05 04												
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 							∽——B——∽									
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
			PRE	FIX CAT.N	O.WITH "L" F	IAS NOT PEEP												
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	l ,	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry										
						FOR SILVER.			H -									
								∕—Wire inspection hole										
\rightarrow	INSTALLATION GUIDE						/—BOLT SIZE											
		DIE CODE = 45 DIE COLOR = Black								5521 5122								
		SIL COLOR - BROCK																
									V.		1							
_	G——G——									Die Çolor								
В																	В	
	CUL)US ROHS							Color coded barrel markings—										
		L	.ISTED		l													
			RE CONNECTORS IVV/2/7/8.E513913															
	-																	l —
		ı	ı						<u> </u>									
											ELES							
۸								HUYA® CELESTRA CORPORATIO 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.							n.			
																	—] ,	
А									WIRE CONNECTORS AND SOLDERING								Α	
										LUGS FOR CODE AND FLEX CABLE								
	00	00 29-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB201434A-250 NTS							ID ANGLE PF	ROJECTION	
	REV	DATE	DWN	CHK		DESCRI			ECN FINIS		DWG NO	186-cp462	7 01	VIT IN	—	⊕ €	\exists	
		I	4	I	I		3	\triangle		2			\perp	11.47	1			'
			•		I		-	7		_			I		•			