_																			
			4				3	7	7		2				1			.	
•					PROERTY OF REPRODUCED				CELESTRA CAT.NO	•	IRE SIZE	BOLT SIZE	B MIN	C	D	G	H		
			FOR WHICH						CAT.NO	CODE	FLEX 125 Navy 1/0 Weld		IVIIIN	±0.04	±0.015	±0.02	±0.01		
									LB201434A	2/0 AWG	275/24 = 111 kcmil		1.31	0.81	0.13	0.75	0.51		
											133/.0282							l	
D																		D	
	l N	IOTE:		DIMENSION CIFIED.	IS ARE IN IN	ICHES UNLESS	OTHERWISE												
		<ol> <li>ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>																	
									B										
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																	
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	INISH:																	
		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry—— H ——									
	 	INSTALLATION GUIDE							Wire inspection hole									_	
	D	IE CODE =	45							BOLT SIZE								7	
		DIE COLOR = Black																	
									1	$\nabla \nabla $	3								
										Die çolor								В	
В																			
	C(UL)US ROHS,							Color coded barrel markings—											
		L	.ISTED		l														
		ZAT	Æ CONNECTORS IVV/2/7/8.E513913																
	ł																		
		I	I	<u> </u>							<u> </u>			000					
										HU		ELES							
										76. Huancun Rd. Zhongcun Towr www.huyaco.com Panyu Dist. Guangzhou 511495.							n.		
Α																	Α		
, (										WIRE CONNECTORS AND SOLDERING								' '	
									LUGS FOR CODE AND FLEX (						ABLI	<u> </u>			
	00	28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					d	N	WROUGHT COPPER LB201434A NTS						ID ANGLE PF	ROJECTION			
1	REV	DATE	DWN	CHK		DESCRI	PTION		ECN F	INISH ELECTRO TII	N PLATE DWG. NO.	186-cp465(	) UN	it INC	сн 📗 🕇	<b>⊕</b> Ł		1	
			4				3		7	2					1				
					•				l				•						