	-	4					3	<b>+</b>	2					1			
l	THE INFORMATION DISCLOSED IN CO	NFIDENCE AND	NOT TO BE					CELESTRA CAT.NO	WIRE		BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	1
	DISLOSED EXCEP	T FOR WHICH F	FURNISHED.					DA2538	250 kcmil	250 Navy 262.6	3/8	2.33	0.93	1.13	1.40	0.63	
										kcmil							
D	NOTE:		DIMENSION CIFIED.	IS ARE II	N INCHES UI	NLESS OT	HERWISE	Color coded marking									D
		LIST	ED BY "UND	DERWRIT	ID J SERIES FERS INC." <i>A</i> LEX/24 STR/	AND "CSA"	FOR USE	Bolt Size									
			ERWISE SP		L" HAS NOT IN THE SUF												
	MATERIAL:	HIGH	H CONDUCT	TIVITY W	ROUGHT CO	OPPER				В		_					
С	FINISH:	SPE	CIFED PLAT	ΓE PER M	NLESS OTHE MIL - T -16366 P" FOR SIL\	6.		-	- /	<i>\</i>	-						С
В	INSTALLATI DIE CODE = DIE COLOR	62 = Yellow	A N	IEB	<b>S</b> 3	RoHS	(€		R	Inspecti	on Hol	e	(				В
Α								HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	_	Ruby Feng					Spec. Initialed.		MATERIAL HIGH-CONDU	DPPER DA	2538			TS THR	ANGLE PE	ROJECTION	
1	REV DATE	DWN 4	CHK	I	DE	SCRIPTI		ECN	ELECTRO TIN I	PLATE DWG. NO. 1	86-cp04	67   U	INIT IN	CH   1	Ψ τ		
		4		I		3		4	۷			1		I			