			4		1		3		<u> </u>		2				1			
'	DISCLO	OSED IN CON	NFIDENCE AND	O NOT TO BE F	PROERTY OF CI REPRODUCED, U				CELESTR.	,,	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01] '
D	DISLOS	SED EXCEPT	FOR WHICH	FURNISHED.			J		DB305601	332	150 Navy 2/0 Wel 325/24 = 131 kcm 133/.0316 259/.0227 427/.0177	t	1.75	0.94	0.14	1.00	0.57	D
	N	OTE:		DIMENSION CIFIED.	S ARE IN INC	HES UNLESS												
_			LIST	ED BY "UND	B,WP AND J S DERWRITERS S AND FLEX/2	INC." AND "C	SA" FOR USE		B I									
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								98° £8° D								
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry H								
\rightarrow	INSTALLATION GUIDE DIE CODE = DIE COLOR =								Wire inspection hole BOLT SIZE									\leftarrow
В		CUL US LISTED WIRE CONNECTORS								Color coded barrel markings								
			ZMVV/2/7/8	.E513913														_
								HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00	04-May-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				d.		WROUGHT COPPER DB305601A NTS						RID ANGLE P	ROJECTION	1		
	REV	DATE	DWN	CHK		DESCRI		,	ECN	ELECTRO TI	N PLATE DWG. NO.	186-cp46	32	nit IN	ICH -	⊕ £		J ,
	4 3							_		2					1			