			4				3	4	7		2				1			
ı	DISCLOS	SED IN CON	IFIDENCE AND	NOT TO BE F	PROERTY OF CEI EPRODUCED, U				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01] '
D	DISLOSE	D EXCEPT	FOR WHICH I	FURNISHED.					DB305601 <i>A</i>		150 Navy 2/0 Wel 325/24 = 131 kcm 133/.0316 259/.0227 427/.0177	l l	1.75	0.94	0.14	1.00	0.57	D
	NOT	ΓE:	SPE	CIFIED.	S ARE IN INCH													
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. B B															_		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								D D									
С		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							-90°									С
	SPECIFED PLATE PER MIL - 1 - 16-366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry H																	
	DIE	INSTALLATION GUIDE DIE CODE = 50 DIE COLOR = Orange								✓ Wire inspection hole ✓ BOLT SIZE								
В		CULUS ROHS LISTED WIRE CONNECTORS ZMV/20/78 E5/49813							Color coded barrel markings									В
_																		_
										HU\ www.huyac		ELES 76. Hua Panyu D	ncun l	Rd. Zh	nongcu	ın Tow		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									А
		23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					WROUGHT COPPER DB305601A NTS						ID ANGLE PI	ROJECTION				
	REV	DATE	DWN	CHK		DESCRI		<u>/</u>	ECN F	ELECTRO TIN	DWG. NO.	186-cp468	32 "	IN	CH 1	(]
			4		I		3	4		2					1			