			4		I			3	\downarrow			2		1		1			
I	DISCL	OSED IN CON	IFIDENCE AND) NOT TO BE F		OF CELESTRA, CED, USED OR	IS		CELEST CAT.N			RE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	G +0.02	H ±0.01]
D	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.					DB301434/		3/0 AWG	150 Navy 2/0 Weld 325/24 = 131 kcmi 133/.0316 259/.0227 427/.0177		1.53	0.96	0.13	0.75	0.58	D
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN	I INCHES UNI													
			LIST	ED BY "UND	DERWRIT	D J SERIES O ERS INC." AN LEX/24 STRAM	ID "CSA"	FOR USE		R									
			OTH			-" HAS NOT P IN THE SUFF													
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry													С					
\rightarrow	D	ISTALLATIO	50					──Wire inspection hole										\triangleleft	
В					Ro	HS			-			BOLT SIZE		rrel ma	rkings		lor		В
																			_
											IUN ww.huyac		ELES 76. Hua Panyu (ancun	Rd. Zh	nongcu	in Tow		-
A								Intel WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										A	
	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER DB301434A-250 NTS									1			
1	REV	DATE	DWN 4	СНК	I	DES	CRIPTI		ECN	FINISH	ELECTRO TIN	I PLATE	86-cp46	85 U	NIT IN	<u>сн</u> 1	ΨĽ]
			4				3		4		Z			1		I			