			4				3	\downarrow		2				1			
ı	DISCLOSE	IN CONFIDE	ENCE AND	NOT TO BE RI	ROERTY OF CEI			CELEST CAT.NO	· ·	VIRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
D	DISLOSED	EXCEPT FOR	R WHICH F	URNISHED.			J	DB301434 <i>A</i>	a-260 3/0 AWG	150 Navy 2/0 Wel 325/24 = 131 kcm 133/.0316 259/.0227 427/.0177		1.39	0.91	0.12	0.75	0.56	D
	NOTE		SPEC	CIFIED.			OTHERWISE										
_		•	LISTI ON C	ED BY "UNDI CODE WIRES	AND FLEX/24	NC." AND "C 4 STRANDEI	SA" FOR USE CABLES.										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FINIS		ELEC SPEC	CTOR-TIN PL	ATE UNLESS E PER MIL - T	OTHERWIS					S _O						С
			SUFF	-IX CAT.NO.	WITH "SP" FO	R SILVER.		Ве	eveled wire ent	ry H							
\rightarrow	DIE C	LLATION G ODE = 50 OLOR = Ora							✓ Wire inspection hole ✓ BOLT SIZE								
В			C UI) US	RoHS,			-		Color co		el ma	rkings	Die Çol	lor		В
			ZMVV/2/7/8.E										J				_
									HU' www.huya	YA	ELES 76. Hua Panyu D	ncun F	Rd. Zh	ongcu	ın Tow		
Α		WIRE CONNECTORS AND SOLDERIN LUGS FOR CODE AND FLEX CABLE										А					
		ug-25 Ru						MATERIAL HIGH-CONDUCTIVITY PRT. NO. DB301434A-260 NTS THRID ANGIO							OJECTION		
	REV D	ATE	DWN	CHK	ı	DESCRI	PTION 3	ECN	ELECTRO T	IN PLATE DWG. NO.	186-cp469	1 00 UN	IN:	сн [†]	Ψτ		1
			+		I		J	4	۷					ı			