		1		1		3	+	2			1		1			
l		THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CEL DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, US			ELESTRA, IS	CELESTRA CAT.NO	WIRE	SIZE	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	. [
	DISLOSED EXCEPT						DA2556-250	CODE 250 kcmil	FLEX 250 Navy 262.6	5/16	2.39	0.79	1.13	1.60	0.63	
D	NOTE:	SPEC 2. ALL I LISTI	CIFIED. DA,DB,LA,LB ED BY "UNDI	s,WP,AL,AS A ERWRITERS	ND J SERIES	S OTHERWISE S OF CAT.NO.S ARE CSA" FOR USE D CABLES.	Color coded marking Bolt Size									D
			ERWISE SPE			P HOLE UNLESS OF THE CAT.NO.										_
С	MATERIAL: FINISH:	ELEC SPEC	CTOR-TIN PL				A B									
В	INSTALLATIO DIE CODE = 0 DIE COLOR =	DN GUIDE 62 = Yellow			RoHs	∶€		R	Inspecti	on Hol	e	6				⊕ В
								HUY www.huyaco	A	ELES 76. Hua Panyu [ancun	Rd. Zh	ongci	ın Tow	_	
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		Ruby Feng		Ce		ards Spec. Initialed.	FON	MATERIAL HIGH-CONDU WROUGHT CO	DPPER DA25	56-250	- 	CALE N7 nit	rs -	RID ANGLE PE	ROJECTION	
	REV DATE	4	CHK		DESCR	3	ECN	electro tin	PLATE DWG. NO. 1	86-cp04	70 0	IN	CH 1	Ψ ^L	7	