			4				3	$\downarrow$			2				1			
'	DISCLO	SED IN CON	FIDENCE ANI	O NOT TO BE RE	ROERTY OF CELES PRODUCED, USED			(	CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
D	DISLOS	SED EXCEPT	FOR WHICH	FURNISHED.				ı	LB301434A	3/0 AWG	150 Navy 2/0 Wel 325/24 = 131 kcm 133/.0316 259/.0227 427/.0177		1.45	0.92	0.13	0.75	0.57	D
	NC	DTE:	SPE 2. ALL	CIFIED. DA,DB,LA,LB,		J SERIES	OF CAT.NO.S ARE											
_			ON PRE	CODE WIRES	RWRITERS INC AND FLEX/24 ST WITH "L" HAS NO	TRANDED OT PEEP I	CABLES. HOLE UNLESS		B									
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER										D							
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry H									
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 50 DIE COLOR = Orange								─Wire inspection hole ─BOLT SIZE									
В	CULUS ROHS								Color coded barrel markings									
		ZMV	V/2/7/8 E513813															_
										HUYA® 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								
А									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
			Ruby Feng							ATERIAL <b>HIGH-COND</b> I WROUGHT O	OPPER LB3	O1434A SCALE NTS THRID ANGLE PROJECTION						
	REV	DATE	DWN 4	CHK		DESCRIF	3	<u> </u>	ECN FI	electro tin	I PLATE	186-cp470	00   0	IN	CH 1	₩ L		<sup>1</sup>